

SECTION 608

SIDEWALKS

608-3.03 CURB RAMPS. Delete subsection in its entirety and replace with the following:

Construct curb ramps according to the details and the locations shown on the Plans. Follow the construction requirements of Subsection 608-3.01. Give the exposed concrete surface a coarse broom finish. Install detectable warnings.

Add new subsection:

608-3.04 DETECTABLE WARNINGS. Construct detectable warnings according to the details and the locations shown on the Plans. Install detectable warning plates by embedding plate flanges into cast in place concrete construction so there are no vertical changes in grade exceeding 0.25 inch or horizontal gaps exceeding 0.5 inch. Align pattern on a square grid in the predominant direction of travel. Install the same type of detectable warning plate throughout the project.

Install cast iron detectable warning plates with a slip resistant surface and coated with either yellow polymer soaked or black asphalt dip finish, with handle or flange on bottom and with truncated dome pattern or approved equal.

Detectable warnings shall be manufactured and installed according to the Americans with Disabilities Act Accessibility Guidelines.

608-4.01 METHOD OF MEASUREMENT. Delete fifth paragraph beginning with: "Curb Ramp" and replace with the following:

Curb Ramp. By each installation, complete in place, including detectable warnings, ramp runs, backing curbs, flares, and landings necessary to provide a single street-level access.