#### **SECTION 00703**

#### ADDITIONAL AIRLINE TENANT DESIGN STANDARDS

### PART 1 GENERAL

## 1.01 GENERAL

Airline tenant improvements shall comply with the requirements of the design standards as well as the additional requirements below.

### 1.02 TICKET COUNTERS

- A. Ticket Counter Shells.
  - 1. ANC will provide ticket counter shells.
  - 2. Ticket counter inserts shall be provided by the airlines.
- B. Ticket Counter Backwalls shall have ANC standard backwall finishes.
- C. Signage shall comply with the Signage and Graphics design criteria as well as the additional requirements below:
  - 1. The maximum logo height is 36".
  - 2. The maximum letter height is 18".
  - 3. The maximum relief or projection of signage is 6".
- D. Back wall graphics
  - 1. Shall be located within the airline identity band.
  - 2. Messages will be limited to corporate logo, copy, and office identification only.
  - 3. Only one logo or carrier name per 20 linear feet of counter length is permitted.
  - 4. Advertisement signs are not permitted on the back wall.
  - 5. Size and space utilized should be proportional to the counter area.
  - 6. Samples of materials and colors shall be submitted to ANC for approval before proceeding with fabrication and installation.

#### E. Liahtina

- 1. Interior illumination sources shall not be used.
- 2. Flashing or blinking lights or signs shall not be used.
- 3. Direct, white colored lighting shall be used.
- F. Temporary signs, banners, or counter signs
  - 1. Shall not be installed unless approved by ANC.
  - 2. Baggage tag information and frequent flyer applications are exempt.
  - 3. Security information required by the FAA or other regulatory agency shall be displayed after approval by ANC.

#### G. Banners

- At airline ticket counters shall only be used to notify passengers of a new service, advise passengers of a new Airline, or the relocation or discontinued Airline operation and only after prior ANC approval.
- 2. Airlines shall only display "new service" (new destinations) for up to 45 days. No promotions, club bonus, campaigns or fares shall be displayed.
- H. Ticketing signage
  - 1. Above the counter shall consist of an airline location sign and surface mounted letters on the continuous "sign box" above the canopy.
  - 2. Airline logos, names, slogans, or other messages are prohibited on these signs.
- I. Sign box letters
  - 1. Shall be limited to the common, carrier name.
  - 2. The letter size shall be 10" high by 3/4" thick or less. Letters shall be all capitals, white, and use Helvetica Medium.

- 3. The letters shall be centered vertically between the top and bottom of the box, and horizontally on panels.
- 4. Locations of signage with current and future monitor locations (built-in) shall be coordinated.
- J. Tenants shall not install lighting in the ticket counters.

## **1.03 QUEUES**

- A. Queue control
  - 1. Queuing at ticket counters shall be controlled by movable, post-mounted barrier straps.
  - 2. The posts shall be 2-1/4" diameter stainless steel posts with a 13" diameter, weighted stainless steel base (with a simple ¼" high taper to the post on a ½" high vertical), and a 4-1/2" high by 2-1/2" diameter stainless steel cap.
  - 3. All stainless steel shall have a satin finish.
  - 4. Retractable barrier straps shall be attached to the post caps.
  - Straps shall be nylon fabric with a solid color, coordinated with the airline's logo and background color.
- B. Queue dimensions
  - 1. Queuing depth shall be limited to a maximum of 25' in front of the ticket counter.
  - 2. A clear path of 15' between the queue area and the structure opposite the ticket counter shall be maintained.
- C. The number and type of check-in accessories, including luggage sizing equipment, podiums, tag dispensers and other equipment may be limited by ANC to maintain safe conditions, queuing and traffic flow, and to minimize clutter.

#### **1.04 GATES**

- A. Podiums
  - 1. Gate Podiums shall be supplied by the airline and represent the airline with their corporate colors and design.
  - 2. Finishes for podiums shall match or exceed the quality standards set by the ANC supplied ticket counter shells.
- B. A backscreen with airline identity and gate flight information shall be located behind each podium.
- C. Electronics in the gate area shall be limited to monitors or LED signs displaying flight information for the airline at the gate.
- D. Signage shall also comply with the Signage and Graphics design criteria.
  - 1. The maximum logo height is 36".
  - 2. The maximum letter height is 18".
  - 3. The maximum relief or projection of signage is 6".
- E. Gate lounge wall graphics.
  - 1. Shall be no lower than 3'-6" or higher than 7'-0" above the finished floor. The maximum logo height is 36". The maximum letter height is 18". The maximum relief or projection of signage is 6".
  - 2. Messages will be limited to corporate logo, copy, and office identification only.
  - 3. Only one logo/carrier name per gate lounge shall be displayed.
  - 4. Flight information signs shall be displayed on the gate lounge counter back wall, but routes or services signs shall not.
  - 5. Size and space utilized shall be proportional to the counter area.
  - 6. Samples of materials and colors shall be submitted to the ANC for approval before proceeding with fabrication and installation.
  - 7. Only "new service" banners are allowed at gate lounge counters. All such banners shall be displayed against a tenant wall or podium. No banners shall hang from the ceiling.

# F. Lighting.

- 1. Interior illumination sources shall not be used.
- 2. Only direct, white colored lighting shall be used.
- 3. Flashing or blinking lights or signs shall not be used.



