


ALASKA CENTRAL REGION LOCATION MAP

NOT TO SCALE



VICINITY MAP

SCALE 1" = 1/2 MILE T 8 N, R 69 W, SEC. 8, 17, & 18 SEWARD MERIDIAN U.S.G.S. BETHEL D-7 (SE, SW) 2017, ALASKA

CONSTRUCTION PLANS

KWETHLUK AIRPORT

KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 **AIRPORT IMPROVEMENT PROGRAM** No. 3-02-0435-002-2023 2023

> **PS&E REVIEW JANUARY 2023**

CONCUR DATE REGIONAL CONSTRUCTION ENGINEER JOEL G. ST. AUBIN, P.E. **APPROVED** DATE LUKE S. BOWLAND, P.E REGIONAL PRECONSTRUCTION ENGINEER **APPROVED** JENELLE R. BRINKMAN. P.E. AVIATION DESIGN GROUP CHIEF **APPROVED** DATE

				-
PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707				
CERT. OF AUTH. NO. AECC111	BY	DATE	REVISION	1_


STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023


1/4/2023


1 of 60


INDEX		INDEX		APPENDIX DRAWINGS			
SHEET TITLE	SHEET No.	SHEET TITLE	SHEET No.	SHEET TITLE	SHEET No.		
COVER	1	RUNWAY LIGHTING DEMO PLAN STA 26+50 TO STA 54+50	37	APPENDIX A			
INDEX	2	RUNWAY AND TAXIWAY LIGHTING PLAN STA 17+50 TO STA 26+50	38	SURVEY CONTROL	AA1 - AA2		
LEGEND AND ABBREVIATIONS	3	RUNWAY LIGHTING PLAN STA 26+50 TO 54+50	39	APPENDIX C			
ESTIMATED QUANTITIES - NTP #1	4	LARGE SCALE APRON PLAN	40	CONSTRUCTION SAFETY AND PHASING PLAN	AC1 - AC14		
ESTIMATED QUANTITIES - NTP #2	5	EDGE LIGHT AND HANDHOLE SCHEDULES	41	APPENDIX K			
PROJECT LAYOUT PLAN	6	LIGHT BASE, HANDHOLE, AND MARKER DETAILS	42	SREB PLANS AND DETAILS			
HAUL ROUTE & STAGING AREA LAYOUT PLAN	7	TRENCH, CONDUIT INSTALLATION, AND COUNTERPOISE DETAILS	43	GENERAL	G1		
DEMOLITION PLAN	8	LIGHTING AND CONNECTOR DETAILS	44	CIVIL	C1 - C4		
CLEARING PLAN	9	WIND CONE DETAILS	45	ARCHITECTURAL	A1 - A6		
TYPICAL SECTIONS	10	ROTATING BEACON DETAILS	46	STRUCTURAL	S1 - S9		
TYPICAL SECTIONS	11	FIELD WIRING SCHEMATIC AND DETAIL	47	MECHANICAL	M1 - M5		
TYPICAL SECTIONS	12	EEB PLAN, ELEVATIONS, EQUIPMENT LIST, AND WALL PENETRATION DETAIL	48	ELECTRICAL	E1 - E10		
REIL PAD PLAN & SECTION	13	EEB ONE-LINE DIAGRAM, GROUNDING DETAIL, AND PANEL SCHEDULE	49				
PAPI PAD PLAN & SECTION	14	AIRFIELD LIGHTING CONTROL DIAGRAM	50				
RUNWAY PLAN AND PROFILE STA 17+60 TO 36+50	15	RW 18 PAPI LAYOUT	51				
RUNWAY PLAN AND PROFILE STA 36+50 TO 54+39	16	RW 36 PAPI LAYOUT	52	STANDAI	RD PLANS		
TAXIWAY PLAN & PROFILE	17	PAPI DETAILS	53	SHEET TITLE	SHEET No.		
TAXIWAY GRADING PLAN	18	PAPI WIRING SCHEMATIC	54				
APRON GRADING PLAN	19	PAPI SHELTER AND HANDHOLE DETAILS	55	SIGN POST BASE AND FOUNDATION	S-31.02		
SUPPLEMENTAL WIND CONE PAD AND ACCESS	20	FAA GUARD WIRE DETAILS AND HANDHOLE SCHEDULE	56				
ACCESS ROAD PLAN AND PROFILE STA 93+90.56 TO STA 102+50	21	FAA TRENCH DETAILS	57				
ACCESS ROAD PLAN AND PROFILE STA 102+50 TO STA 117+50	22	REIL PLOT PLANS	58				
ACCESS ROAD PLAN AND PROFILE STA 117+50 TO STA 132+00	23	REIL DETAILS	59				
ACCESS ROAD PLAN AND PROFILE STA 132+00 TO 147+00	24	REIL WIRING SCHEMATIC	60	REFERENCE	DRAWINGS		
ACCESS ROAD PLAN AND PROFILE STA 147+00 TO STA 156+87.08	25	ELECTRIC UTILITY PLANS		SHEET TITLE	SHEET No.		
CULVERT PLAN AND PROFILE - NORTHERN CROSSING	26	UTILITY LEGEND AND NOTES	UE1				
CULVERT PLAN AND PROFILE - SOUTHERN CROSSING	27	UTILITY/ACCESS ROAD OVERALL PLAN	UE2				
CIVIL DETAILS	28	LARGE SCALE UTILITY PLAN AT APRON	UE3				
REIL AND PAPI FOUNDATION DETAILS	29	LARGE SCALE UTILITY PLAN AT SCHOOL	UE4				
DEADMAN DETAILS	30	UTILITY POLE EMBEDMENT AND GUY DETAILS	UE5				
SIGN SUMMARY	31	UTILITY STAKING SHEET	UE6				
SIGN DETAILS	32						
SEGMENTED CIRCLE DETAILS	33						
SEGMENTED CIRCLE DETAILS	34						
LIGHTING NOTES AND LEGEND	35						
RUNWAY LIGHTING DEMO PLAN STA 17+00 TO STA 26+50	36						
		PLANS DEVELOPED BY: R&M CONSULTANTS, INC.		STATE OF ALASKA DEPARTMENT OF TRANSPORTATION	KWETHLUK AIRPORT KWETHLUK, ALASKA DATE: 1/5/202		
		9101 VANGUARD DR. ANCHORAGE, AK 99507		AND PUBLIC FACILITIES CENTRAL REGION	AIRPORT REHABILITATION PROJECT No. CFAPT00682 SHFFT:		
		(907) 522-1707 CERT. OF AUTH. NO. AECC111 BY DATE	REVISION	4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590	AIP No. 3-02-0435-002-2023 INDEX 2 OF 6		





			<u> LJII</u>	MATED QUANTITIE	<u>. </u>	<u> </u>				
No.	ITEM	UNIT QUANTITY	No.	ITEM	UNIT	QUANTITY	No.	ITEM	UNIT	QUANTIT
F162.010.0008	8-FEET CHAIN-LINK FENCE	LF 106	L107.010.0008	8-FEET LIGHTED WIND CONE, IN PLACE	EA	1	P154.020.0000	SUBBASE COURSE	TON	2,239
F162.030.0004	SINGLE SWING GATE, 4-FEET WIDE	EA 4	L107.011.0008	8-FEET LIGHTED WIND CONE, SUPPLEMENTAL, IN PLACE	EA	1	P167.010.0000	DUST PALLIATIVE	SY	64,822
F170.010.0000	STEEL BOLLARD	EA 52	L108.010.2008	UNDERGROUND CABLE #8 AWG, COPPER, 5kV FAA TYPE C, L-824	LF	9,037	P299.020.0000	CRUSHED AGGREGATE SURFACE COURSE	TON	38,802
G100.010.0000	MOBILIZATION AND DEMOBILIZATION	LS ALL REQ'D	L108.030.0006	#6 BARE COPPER GROUND CONDUCTOR	LF	15,607	P299.070.0000*	CRUSHED AGGREGATE SURFACE COURSE STOCKPILE	TON	200
G105.010.0000*	POST AWARD CONFERENCE	LS ALL REQ'D	L108.050.1010	UNDERGROUND CABLE #10 AWG, COPPER, 600V, TYPE C, L-824	LF	1,170	P620.070.0000	TEMPORARY RUNWAY & TAXIWAY PAINTING	LS	ALL REQ'D
G115.010.0000	WORKERS MEALS AND LODGING, OR PER DIEM	LS ALL REQ'D	L108.070.0000	GROUND ROD	EA	25	P640.020.0000	SEGMENTED CIRCLE (PANEL-TYPE)	LS	ALL REQ'D
G130.010.0000	FIELD OFFICE	LS ALL REQ'D	L109.030.0000	ELECTRICAL ENCLOSURE AND FOUNDATION IN PLACE	EA	1	P641.010.0000	EROSION, SEDIMENT, AND POLLUTION CONTROL ADMINISTRATION	LS	ALL REQ'D
G130.020.0000	FIELD LABORATORY	LS ALL REQ'D	L109.040.0000	INSTALLATION OF ELECTRICAL EQUIPMENT IN NEW OR EXISTING STRUCTURE	EA	1	P641.050.0000	TEMPORARY EROSION, SEDIMENT, AND POLLUTION CONTROL BY DIRECTIVE	cs	ALL REQ'D
G130.040.0000	MEAL	EA 1,890	L110.050.1004	RIGID STEEL CONDUIT, 4-INCH	LF	297	P641.060.0000	WITHHOLDING	CS	ALL REQ'D
G130.050.0000	LODGING	EA 540	L110.080.1002	HDPE CONDUIT, 2-INCH	LF	8,328	P641.070.0000	SWPPP MANAGER	LS	ALL REQ'D
G130.060.0000	NUCLEAR TESTING EQUIPMENT STORAGE SHED	EA 1	L125.020.0000	REGULATOR, L-828	EA	1	P650.010.0000	AIRCRAFT TIE-DOWN	EA	16
G130.110.0000	FIELD COMMUNICATIONS	CS ALL REQ'D	L125.030.0000	MEDIUM INTENSITY RUNWAY EDGE AND THRESHOLD LIGHT, L -861 AN L $-861E$	D EA	47	P660.030.0000	REFLECTIVE MARKER, TYPE II	EA	20
G131.010.0000	ENGINEERING TRANSPORTATION (TRUCK)	EA 1	L125.040.0000	TAXIWAY EDGE LIGHT, L-861T	EA	14	P670.010.0000	HAZARD MARKER BARRIER, PLASTIC	EA	31
G131.020.0000	ENGINEERING TRANSPORTATION (ATV)	EA 2	L125.070.0000	REMOVE RUNWAY AND TAXIWAY LIGHT	EA	64	P671.010.0000	RUNWAY CLOSURE MARKER, VINYL MESH	EA	8
G135.010.0000	CONSTRUCTION SURVEYING BY THE CONTRACTOR	LS ALL REQ'D	L125.150.0000	HANDHOLE, L-867, SIZE B	EA	9	P671.020.0000	RUNWAY CLOSURE MARKER, ILLUMINATED	EA	2
G135.020.0000	EXTRA THREE PERSON SURVEY PARTY	HR 65	L125.170.0000	SPARE PARTS	cs	ALL REQ'D	P681.010.0000	GEOTEXTILE, SEPARATION	SY	1,226
G135.050.0000	CONTRACTOR FURNISHED ENGINEERING TOOLS	CS ALL REQ'D	L125.180.0000	TEMPORARY RUNWAY LIGHTING SYSTEM	LS	ALL REQ'D	P687.010.0010	GEOGRID, STABILIZATION, CLASS 1	SY	801
G150.010.0070	EQUIPMENT RENTAL, DOZER 70-HP MINIMUM	HR 50	L132.010.0010	INSTALL APPROACH LIGHTING AIDS, PAPI	LS	ALL REQ'D	\$142.050.0010	EQUIPMENT STORAGE BUILDING NO.1	LS	ALL REQ'D
G300.010.0000	CPM SCHEDULING	LS ALL REQ'D	L132.010.0020	INSTALL APPROACH LIGHTING AIDS, REIL	LS	ALL REQ'D	\$142.050.0020	EQUIPMENT STORAGE BUILDING NO.2	LS	ALL REQ'D
G700.010.0000	AIRPORT FLAGGER	CS ALL REQ'D	L132.020.0010	REMOVE APPROACH LIGHTING AIDS, PAPI	LS	ALL REQ'D	\$142.120.0000*	AIR COMPRESSOR	LS	ALL REQ'D
G710.010.0000	HIGHWAY TRAFFIC MAINTENANCE	LS ALL REQ'D	L132.020.0020	REMOVE APPROACH LIGHTING AIDS, REIL	LS	ALL REQ'D	\$143.010.1000	HEATING FUEL TANK, 1000 GAL	EA	1
G710.020.0000	HIGHWAY FLAGGER	CS ALL REQ'D	P151.010.0000	CLEARING	AC	0.05	\$143.020.0000*	FUEL	LS	ALL REQ'D
G710.030.0000	HIGHWAY TRAFFIC PRICE ADJUSTMENT	CS ALL REQ'D	P151.030.0000	CLEARING AND GRUBBING	AC	9.80	S143.040.0000*	ELECTRIC DISPENSING SYSTEM	EA	1
G710.040.0000	HIGHWAY TRAFFIC CONTROL	CS ALL REQ'D	P152.010.0000	UNCLASSIFIED EXCAVATION	CY	5,451	\$143.060.0000	SPILL PREVENTION CONTROL AND COUNTERMEASURE PLAN	LS	ALL REQ'D
L101.020.0000	ROTATING BEACON, MEDIUM INTENSITY, L-801A	EA 1	P152.200.0000	BORROW	TON	5,107	U500.010.0000	ELECTRICAL POWER SYSTEM	LS	ALL REQ'D
L103.010.0030	30-FEET HINGED POLE BEACON TOWER	EA 1	P152.275.0000	POROUS BACKFILL	TON	6,534	* NON-PARTIC	CIPATING ITEM		
			OF ALVEN							
				PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR.			DEPARTMENT	ATE OF ALASKA F OF TRANSPORTATION IN IC FACILITIES KWETHLUK A KWETHLUK A AIRPORT REHABI	LASKA LITATION	DATE: 1/4/2023
			thew I. Majoros CE - 14441	ANCHORAGE, AK 99507 (907) 522-1707 ERT. OF AUTH. NO. AECC111 BY DATE			CE	JBLIC FACILITIES INTRAL REGION VE., ANCHORAGE ALASKA 99502 PROJECT No. CF AIP No. 3-02-043	APT00682 5-002-2023	SHEET: 4 OF 60




















SUPPLEMENTAL WIND CONE ACCESS ROAD TYPICAL SECTION

* SURCHARGED MATERIAL TO BE CUT BACK FOR CASC

- 1. APPLY DUST PALLIATIVE TO ALL AREAS RECEIVING NEW CASC.
- 2. PLACE 4" POROUS BACKFILL ON ALL DISTURBED SLOPES.
- 3. IN AREAS WHERE EXCAVATION WILL NOT OCCUR THE EXISTING EMBANKMENT SHALL BE SCARIFIED DOWN TO 2 INCHES PRIOR TO FILL BEING PLACED. THIS WORK IS SUBSIDIARY TO UNCLASSIFIED EXCAVATION AND WILL NOT BE MEASURED FOR PAYMENT.
- 4. SURCHARGE MATERIAL SHALL BE PLACED FOR A MINIMUM OF ONE SEASONAL FREEZE THAW CYCLE. SURCHARGE MATERIAL SHALL CONSIST OF SUITABLE MATERIAL.



PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT OF AUTH NO AECC111 BY DATE REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT

KWETHLUK, ALASKA

AIRPORT REHABILITATION


PROJECT No. CFAPT00682


AIP No. 3-02-0435-002-2023


TYPICAL SECTIONS


1/4/2023


12 of 60




















































SECTION A/29

NOTES:

1. CONCRETE AT 4000 PSI COMPRESSIVE STRENGTH AT 28 DAYS. SLUMP: 3 INCHES @ 60°F ± 1 INCH

WITH 1 $\frac{1}{2}$ INCH MAXIMUM AGGREGATE

- 2. USE CONCRETE IN CONFORMANCE WITH SPECIFICATION P-610.
- 3. REINFORCING STEEL ASTM A615, GRADE 60, DEFORMED STEEL BARS.
- 4. PLACE REINFORCEMENT 2" CLEAR FROM SURFACE OF CONCRETE.
- 5. CHAMFER ALL EXPOSED CONCRETE CORNERS 1".
- 6. TOP OF BOTH REIL AND PAPI PADS SHALL BE LEVEL AND 1" ABOVE SURROUNDING GRADE.
- 7. DRILL ANCHOR BOLTS AND INSTALL ADHESIVE ANCHORS AFTER UNITS HAVE BEEN ACCURATELY LOCATED.



PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT. OF AUTH. NO. AECC111 BY DATE REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT


KWETHLUK, ALASKA

AIRPORT REHABILITATION

PROJECT No. CFAPT00682


AIP No. 3-02-0435-002-2023 REIL AND PAPI FOUNDATION DETAILS

1/4/2023 29 of 60




-#4 @ 11" ON CENTER, EACH WAY, TOP AND BOTTOM







SECTION B/29









NOTES:

- 1. FABRICATE SIGNS FROM 0.125" THICK ALUMINUM SHEETING.

- INSTALL ON FRANCIBLE COUPLING SYSTEM WITH CONCRETE SIGN POST FOUNDATION. SEE ALASKA STANDARD PLAN S-31.02.



PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT. OF AUTH. NO. AECC11 DATE **REVISION**

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION**

PHONE (907) 269-0590

KWETHLUK 1.4 MILE SIGN (S4) DETAILS

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023


1/4/2023 31 of 60

SIGN LOCATIONS ARE APPROXIMATE AND SUBJECT TO FIELD ADJUSTMENTS BY THE ENGINEER 3. REMOVE EXISTING POST AND INSTALL NEW POSTS FROM AIRPORT SIGN SUMMARY TABLE.

4111 AVIATION AVE., ANCHORAGE ALASKA 99502 SIGN SUMMARY

- 1. ONLY USE SQUARE STEEL TUBES TO SUPPORT SIGNS MOUNTED ON SINGLE POSTS.
- 2. INSTALL WINDBEAM ON SIGNS 36 INCHES WIDE AND WIDER.
- 3. THE ENGINEER MAY APPROVE OTHER FRAMING MEMBERS. SUBMIT DOCUMENTS THAT DETAIL THE FRAME'S CROSS SECTION AND STRENGTH, AND METHOD OF ATTACHING THE FRAME TO A POST.
- 4. USE FRAMING MEMBERS MADE FROM ALUMINUM ALLOY 6061-T6.
- 5. EACH FRAMING MEMBER SHALL BE ONE CONTINUOUS PIECE.
- 6. ATTACH FRAMING MEMBERS TO THE SIGN PANELS WITH RIVETS OR AN ENGINEER APPROVED, DOUBLE SIDED, HIGH STRENGTH, ADHESIVE TAPE.
- 7. WITH THE ADHESIVE TAPE, INSTALL TWO RIVETS IN BOTH ENDS OF EACH FRAMING MEMBER, AND ATTACH THE FRAMING MEMBERS TO THE SIGN PANELS ACCORDING TO THE TAPE
 - MANUFACTURER'S WRITTEN INSTRUCTIONS, INCLUDING:

 A. THE CLEANING AND HANDLING OF THE SIGN PANELS AND FRAMING MEMBERS.
 - THE APPLICATION OF THE ADHESIVE TAPE.
- 8. WHEN RIVETS ARE USED TO ATTACH FRAMING MEMBERS, INSTALL 2 RIVETS IN EACH END AND THE BALANCE ON 8" MAXIMUM CENTERS.
- 9. USE 3/6" DIAMETER RIVETS CONFORMING TO ALUMINUM ALLOY 6061-T6 FOR COLD DRIVEN RIVETS, OR ALUMINUM ALLOY 6061-T43 FOR HOT DRIVEN RIVETS.
- 10. THE BRACKETS USED ON EVEN INCH SIZE TUBES MAY ALSO BE USED ON TUBES ½" SMALLER IN SIZE.
- 11. POST LENGTHS SHALL BE DETERMINED IN THE FIELD BY THE CONTRACTOR USING THE CRITERIA FOR RURAL ROADS, UNLESS DETERMINED OTHERWISE BY THE ENGINEER.
- 12. REMOVE AND DISPOSE OF ALL EXISTING SIGNS, POSTS, AND FOUNDATIONS SCHEDULED FOR REPLACEMENT.



BY

DATE

REVISION

AND PUBLIC FACILITIES

CENTRAL REGION

4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023

SIGN DETAILS

32 of 60


9101 VANGUARD DR.


ANCHORAGE, AK 99507

(907) 522-1707

CERT OF AUTH NO AECC11

CE - 14441






PEAK GUSSET PLATE PANEL MOUNTING FRAME

SEGMENTED CIRCLE NOTES:

- 1. ALL STRUCTURAL MEMBERS OF PANEL ASSEMBLY ARE GS-PST (GALVANIZED SQUARE PERFORATED STEEL TUBING), SIZE AS INDICATED IN DRAWING, IN CONFORMANCE WITH SECTION P-640.
- 2. ALL BOLTS, NUTS, AND WASHERS SHALL CONFORM TO FASTENER SPECIFICATION TABLE INCLUDED IN THIS PLAN SET. ALL BOLTS USED IN PANEL ASSEMBLY SHALL BE %" DIA. C LENGTH CALLED OUT IN PLANS, UNLESS OTHERWISE NOTED. FOR EACH BOLT INCLUDE 1 EA %" WASHERS (%6" ID X 1" OD) ONE AT THE BOLT HEAD AND ONE AT THE NUT.
- 3. GUSSET PLATES SHALL CONFORM TO AIRPORT SPECIFICATION P-640 INCLUDED WITH THIS PLAN SET.
- 4. FINISH HEIGHT OF ALL INSTALLED PANEL ASSEMBLIES COMPRISING A SINGLE SEGMENTED CIRCLE SHALL BE UNIFORM WITH A MAXIMUM VARIANCE OF 6" THROUGHOUT CIRCLE LAYOUT, UNLESS OTHERWISE APPROVED BY THE ENGINEER.
- 5. PANEL ASSEMBLIES ARE TO BE REMOVABLE FROM EMBEDMENT TUBES FOR MAINTENANCE PURPOSES.
- 6. DIMENSIONS LABELED "(REF)" ARE FOR INFORMATIONAL PURPOSES ONLY.
- 7. INSTALLATION OF POSTS MAY REQUIRE MINOR TRENCHING IF OCCASIONAL ROCK IS ENCOUNTERED IN THE PAD BORROW EMBANKMENT. BACKFILL EXCAVATED MATERIAL AND RESTORE LEVEL SURFACE. THIS WORK IS SUBSIDIARY TO THE RESPECTIVE P-640 PAY ITEM AT EACH LOCATION.



LOWER GUSSET PLATE PANEL MOUNTING FRAME NTS

FASTENER SPEC	IFICATION TABLE
FASTENER TYPE	STEEL HOT DIPPED GALVANIZED
BOLTS	ASTM A 307
NUTS	ASTM A 563
WASHERS	ASTM F 844



R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT. OF AUTH. NO. AECC1111 BY DATF REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT
KWETHLUK, ALASKA
AIRPORT REHABILITATION
PROJECT No. CFAPT00682
AIP No. 3-02-0435-002-2023
SEGMENTED CIRCLE DETAILS

1/4/2023 34 of 60 2. THE CONTRACTOR SHALL RESTORE GRADE AND FINISH SURFACES DISTURBED BY THE REMOVAL OF STRUCTURES. THIS WORK SHALL BE SUBSIDIARY TO THE CONTRACT AND NO SEPARATE PAYMENT WILL BE MADE.

DEMOLISHED FIXTURES, TRANSFORMERS, REGULATOR, WIND CONES, AND BEACON SHALL BE SALVAGED AND OFFERED TO DOT MAINTENANCE EQUIPMENT DEEMED OF NO SALVAGE VALUE BY DOT MAINTENANCE PERSONNEL AND ALL OTHER FOUIPMENT AND MATERIALS NOT LISTED ABOVE, INCLUDING LIGHT BASES, HANDHOLES, WIND CONE FOUNDATIONS, WIRE, AND RACEWAYS, SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL STATUTES. DISPOSAL SHALL NOT TAKE PLACE IN KWETHLUK.

4. REMOVAL OF EXISTING CONDUCTORS AND GROUND WIRE SHALL BE SUBSIDIARY TO THE REMOVAL OF THE ASSOCIATED EQUIPMENT AND NO SEPARATE PAYMENT WILL BE MADE.

5. REMOVAL OF HANDHOLES, IF NOT SUBSIDIARY TO OTHER ITEMS, SHALL BE PAID UNDER ITEM L125.070.0000.

6. REMOVAL OF REFLECTIVE MARKERS AND CONES SHALL BE SUBSIDIARY TO ITEM L125.070.0000 AND NO SEPARATE PAYMENT WILL BE MADE.

7. LOCATE EXISTING UNDERGROUND UTILITIES PRIOR TO COMMENCING WORK.

DEMOLITION SHEET NOTES:

REMOVE RUNWAY EDGE LIGHTS, THRESHOLD LIGHTS, TAXIWAY LIGHTS, BASES, HANDHOLES, TRANSFORMERS, CONDUIT, AND

ABBREVIATIONS

AMERICAN WIRE GAUGE BARE COPPER GROUND CONDUIT

CABC CRUSHED AGGREGATE BASE COURSE CCR CONSTANT CURRENT REGULATOR CONSTRUCTION SAFETY AND PHASING PLAN CSPF CU

COPPER DIRECT EARTH BURY DEGREES

DEG EEB ELECTRICAL EQUIPMENT BUILDING

EXISTING TO REMAIN FAA FEDERAL AVIATION ADMINISTRATION

FT HDPE

BCU

DEB

ICC

HIGH DENSITY POLYETHYLENE INDIVIDUAL CONTROL CABINET (REIL)

KILOVOLT KW KII OWATT

LED LIGHT EMITTING DIODE

LFMC LIQUIDTIGHT FLEXIBLE METAL CONDUIT

LTS

NATIONALLY RECOGNIZED TESTING LABORATORY NRTI MAX MAXIMUM

MIN MINIMUM

MEDIUM INTENSITY RUNWAY LIGHTING MIRI MEDIUM INTENSITY TAXIWAY LIGHTING MITL

ON CENTER UON UNLESS OTHERWISE NOTED

PAPI PRECISION APPROACH PATH INDICATOR

PCT PERCENT

RUNWAY END IDENTIFIER LIGHT RFII RSC. RMC RIGID GALVANIZED STEEL CONDUIT RUNWAY

RW(X)RW CIRCUIT, NUMBER IN () INDICATES # OF CONDUCTORS SERIES CUT OUT

SNOW REMOVAL EQUIPMENT BUILDING SREB

STAINLESS STEEL SS

STA **THRESHOLD** TOP OF CONCRETE TOC

TW CIRCUIT, NUMBER IN () INDICATES # OF CONDUCTORS TW(X)

TAXIWAY XFMR TRANSFORMER **GENERAL NOTES:**

1. CONDUITS AND LIGHT BASES SHALL BE INSTALLED PRIOR TO PLACEMENT OF FINISH COURSE.

2. REMOVE POWER FROM LIGHTING CIRCUITS DURING ASSOCIATED WORK, RESTORE POWER WHEN WORK IS COMPLETE.

3. AIRFIELD LIGHTING CABLE SHALL BE #8 AWG, 5kV, FAA TYPE "C" AIRPORT CABLE.

4. CONNECT HDPE CONDUIT TO DISSIMILAR CONDUIT USING A LISTED TRANSITION FITTING. HDPE TO HDPE CONNECTIONS SHALL BE BUTT WELDED.

5. PROVIDE LIGHT BASES WITH HUB CONFIGURATIONS TO ACCOMMODATE THE LAYOUT AS SHOWN IN THE PLANS. ROUTE CONDUIT FROM POINT TO POINT, IN A STRAIGHT LINE, EXCEPT AS REQUIRED TO AVOID AN OBSTRUCTION.

6. ALL BOLTS, NUTS, AND THREADED SURFACES SHALL BE COATED WITH ANTI-SEIZE LUBRICANT PER SPECIFICATIONS.

7. HANDHOLE LOCATIONS MAY BE FIELD ADJUSTED AS APPROVED BY THE ENGINEER.

8. CONDUIT ROUTING SHOWN FOR CLARITY. ROUTE CONDUITS ON SHOULDER. CONDUITS THAT RUN IN CLOSE PROXIMITY MAY BE INSTALLED IN SAME TRENCH.

9. PROVIDE LIGHTNING PROTECTION COUNTERPOISE FOR ALL RUNWAY AND TAXIWAY LIGHTING CIRCUITS PER DETAIL 2/43 AND 5/43. #6 BARE COPPER WIRE IS PAID UNDER ITEM L108.030.0006, GROUND RODS ARE PAID UNDER ITEM L108.070.0000.

10. CONTRACTOR SHALL PROVIDE A LIST OF PROPOSED SPARE PARTS AND THE COST FOR EACH CATEGORY TO THE ENGINEER FOR REVIEW PRIOR TO PLACING THE ORDER FOR THE PARTS. QUANTITIES SHALL BE REDUCED IF NECESSARY UNTIL THE COSTS ARE WITHIN THE LIMITS OF THE FAA REQUIREMENTS. SEE SECTION L-125 FOR ADDITIONAL INFORMATION.

11. SLOPE CONDUITS TO DRAIN TO LOW SPOT. PROVIDE 2" HDPE CONDUIT DRAINS TO DAYLIGHT AS SHOWN OR AS DIRECTED BY THE ENGINEER, INSTALL CONDUIT TO PROVIDE POSITIVE DRAINAGE FROM LIGHT BASES. PROVIDE 1/4" GALVANIZED SCREEN, FIRMLY ATTACH TO OPEN END OF DRAIN CONDUIT WITH STAINLESS STEEL BAND CLAMP. DRAIN CONDUITS ARE PAID UNDER ITEM L110.080.1002. SCREENS AND BAND CLAMPS SHALL BE SUBSIDIARY TO L110.080.1002 AND NO SEPARATE PAYMENT WILL BE MADE.

LEGEND:			
<u>EXISTING</u>	DEMOLITION	<u>NEW</u>	
			2" HDPE CONDUIT. HASH MARKS INDICATE NUMBER OF NEW #8 AWG. 5KV AIRPORT CABLES, TYPE "C", PLUS ONE #6 BARE COPPER GROUND CONDUCTOR.
			2" HDPE CONDUIT, THROUGH A 4" RSC SLEEVE. HASH MARKS INDICATE NUMBER OF NEW #8 AWG. 5KV AIRPORT CABLES, TYPE "C", PLUS ONE #6 BARE COPPER GRÖUND CONDUCTOR.
\circ	×	$^{R}\!$	THRESHOLD LIGHT, GREEN/RED
\circ	× × ×	w _C Y	RUNWAY EDGE LIGHT, WHITE/YELLOW
\circ	×	Ф	RUNWAY EDGE LIGHT, WHITE/WHITE
B	×	8	TAXIWAY EDGE LIGHT
\bigcirc	×	•	HANDHOLE, L-867
	R		WIND CONE, L-807
>0€	⇒o€`	>0€	ROTATING BEACON
1	人	人	RADIO CONTROLLER ANTENNA
\$=	*	♦	FAA REIL IDENTIFIER (LAMP HEAD) AND INDIVIDUAL CONTROL CABINET (ICC)
	×		FAA PAPI LIGHT HOUSING ASSEMBLY (LHA)
lacksquare	⊠	(CONCRETE HANDHOLE
	, ,	∇	3/4" X 10' COPPER COATED GROUND ROD
		RXXX	LIGHT OR HANDHOLE NUMBER "X" - SEE SCHEDULE
		(TEMPORARY RUNWAY EDGE LIGHT
		₿	TEMPORARY TAXIWAY EDGE LIGHT
		lacklacklack	TEMPORARY THRESHOLD LIGHT
OT		——от——	OVERHEAD TELEPHONE
OE		—— ОЕ——	OVERHEAD ELECTRIC
UGE		UGE	UNDERGROUND ELECTRIC

UNDERGROUND FAA POWER AND COMM

LECENIE



MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 (907) 274-2622 CERTIFICATE OF AUTHORIZATION NO. AECC578

BY DATE REVISION DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES **CENTRAL REGION**

4111 AVIATION AVE., ANCHORAGE ALASKA 99502

PHONE (907) 269-0590


KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682


1/4/2023


35 of 60


STATE OF ALASKA


AIP No. 3-02-0435-002-2023 LIGHTING NOTES AND LEGEND











HMO	HMO	97.0
Designed By:	Drawn By:	

KWETHLUK AIRPORT TAXIWAY EDGE LIGHT SCHEDULE													
LIGHT#	IGHT# LENS TYPE LAMP XF		XFMR	ALIGNMENT	STATION	OFFSET	CONE COLOR						
T1	BLUE	L-861T	45	45	TW	72+24.00	26.15 L	BLUE					
T2	BLUE	L-861T	45	45	TW	72+11.00	22.50 L	BLUE					
Т3	BLUE	L-861T	45	45	TW	72+11.00	22.50 R	BLUE					
T4	BLUE	L-861T	45	45	TW	72+24.00	26.15 R	BLUE					
T5	BLUE	L-861T	45	45	TW	71+41.75	22.50 R	BLUE					
T6	BLUE	L-861T	45	45	TW	70+72.50	22.50 R	BLUE					
T7	BLUE	L-861T	45	45	TW	70+54.82	29.82 R	BLUE					
T8	BLUE	L-861T	45	45	TW	70+55.50	47.50 R	BLUE					
Т9	BLUE	L-861T	45	45	TW	70+50.50	47.50 R	BLUE					
T10	BLUE	L-861T	45	45	TW	70+50.50	47.50 L	BLUE					
T11	BLUE	L-861T	45	45	TW	70+55.50	47.50 L	BLUE					
T12	BLUE	L-861T	45	45	TW	70+54.82	29.82 L	BLUE					
T13	BLUE	L-861T	45	45	TW	70+72.50	22.50 L	BLUE 1					
T14	BLUE	L-861T	45	45	TW	71+41.75	22.50 L	BLUE					

	KWET	HLUK AIRPORT I	HANDHOLE SCHE	DULE
NO.	SYSTEM	PAY ITEM	REMARKS	LOCATION
BH1	ROT. BEACON	L125.150.0000	PER EACH	FIELD LOCATE
HH1	RW/TW LTG	L125.150.0000	PER EACH	FIELD LOCATE
HH2	RW/TW LTG	L125.150.0000	PER EACH	FIELD LOCATE
HH3	RW/TW LTG	L125.150.0000	PER EACH	FIELD LOCATE
WC1	WIND CONE	L125.150.0000	PER EACH	FIELD LOCATE
WC2	WIND CONE	L125.150.0000	PER EACH	FIELD LOCATE
WC3	WIND CONE	L125.150.0000	PER EACH	FIELD LOCATE
WC4	WIND CONE	L125.150.0000	PER EACH	FIELD LOCATE
WC5	WIND CONE	L125.150.0000	PER EACH	FIELD LOCATE

KWETHLUK AIRPORT RUNWAY EDGE LIGHT SCHEDULE													
UNIT#	LENS	TYPE	WATTS	XFMR	ALIGNMENT	STATION	OFFSET	CONE COLOR					
R1	W/Y	L-861	45	45	RW	25+58.06	47.50 L	WHITE/YELLOW					
R2	W/Y	L-861	45	45	RW	27+47.41	47.50 L	WHITE/YELLOW					
R3	W/Y	L-861	45	45	RW	29+36.76	47.50 L	WHITE/YELLOW					
R4	W/Y	L-861	45	45	RW	31+26.12	47.50 L	WHITE/YELLOW					
R5	W/Y	L-861	45	45	RW	33+15.47	47.50 L	WHITE/YELLOW					
R6	W/Y	L-861	45	45	RW	35+04.82	47.50 L	WHITE/YELLOW					
R7	Y/W	L-861	45	45	RW	36+94.18	47.50 L	YELLOW/WHITE					
R8	Y/W	L-861	45	45	RW	38+83.53	47.50 L	YELLOW/WHITE					
R9	Y/W	L-861	45	45	RW	40+72.88	47.50 L	YELLOW/WHITE					
R10	Y/W	L-861	45	45	RW	42+62.24	47.50 L	YELLOW/WHITE					
R11	Y/W	L-861	45	45	RW	44+51.59	47.50 L	YELLOW/WHITE					
R12	Y/W	L-861	45	45	RW	46+40.94	47.50 L	YELLOW/WHITE					
R13	Y/W	L-861	45	45	RW	48+30.29	47.50 L	YELLOW/WHITE					
R14	Y/W	L-861	45	45	RW	50+19.65	47.50 L	YELLOW/WHITE					
R15	R/G	L-861E	45	45	RW	52+09.00	47.50 L	RED/GRN					
R16	R/G	L-861E	45	45	RW	52+09.00	57.50 L	RED/GRN					
R17	R/G	L-861E	45	45	RW	52+09.00	67.50 L	RED/GRN					
R18	R/G	L-861E	45	45	RW	52+09.00	77.50 L	RED/GRN					
R19	R/G	L-861E	45	45	RW	52+09.00	77.50 R	RED/GRN					
R20	R/G	L-861E	45	45	RW	52+09.00	67.50 R	RED/GRN					
R21	R/G	L-861E	45	45	RW	52+09.00	57.50 R	RED/GRN					
R22	R/G	L-861E	45	45	RW	52+09.00	47.50 R	RED/GRN					
R23	Y/W	L-861	45	45	RW	50+19.65	47.50 R	YELLOW/WHITE					
R24	Y/W	L-861	45	45	RW	48+30.29	47.50 R	YELLOW/WHITE					
R25	Y/W	L-861	45	45	RW	46+40.94	47.50 R	YELLOW/WHITE					
R26	Y/W	L-861	45	45	RW	44+51.59	47.50 R	YELLOW/WHITE					
R27	Y/W	L-861	45	45	RW	42+62.24	47.50 R	YELLOW/WHITE					
R28	Y/W	L-861	45	45	RW	40+72.88	47.50 R	YELLOW/WHITE					
R29	Y/W	L-861	45	45	RW	38+83.53	47.50 R	YELLOW/WHITE					
R30	Y/W	L-861	45	45	RW	36+94.18	47.50 R	YELLOW/WHITE					
R31	W/Y	L-861	45	45	RW	35+04.82	47.50 R	WHITE/YELLOW					
R32	W/Y	L-861	45	45	RW	33+15.47	47.50 R	WHITE/YELLOW					
R33	W/Y	L-861	45	45	RW	31+26.12	47.50 R	WHITE/YELLOW					
R34	W/Y	L-861	45	45	RW	29+36.76	47.50 R	WHITE/YELLOW					
R35	W/Y	L-861	45	45	RW	27+47.41	47.50 R	WHITE/YELLOW					
R36	W/Y	L-861	45	45	RW	25+58.06	47.50 R	WHITE/YELLOW					
R37	W/Y	L-861	45	45	RW	23+68.71	47.50 R	WHITE/YELLOW					
R38	W/Y	L-861	45	45	RW	21+79.35	47.50 R	WHITE/YELLOW					
R39	G/R	L-861E	45	45	RW	19+90.00	47.50 R	GRN/RED					
R40	G/R	L-861E	45	45	RW	19+90.00	57.50 R	GRN/RED					
R41	G/R	L-861E	45	45	RW	19+90.00	67.50 R	GRN/RED					
R42	G/R	L-861E	45	45	RW	19+90.00	77.50 R	GRN/RED					
R43	G/R	L-861E	45	45	RW	19+90.00	47.50 L	GRN/RED					
R44	G/R	L-861E	45	45	RW	19+90.00	57.50 L	GRN/RED					
R45	G/R	L-861E	45	45	RW	19+90.00	67.50 L	GRN/RED					
R46 G/R L-861E 45				45	RW	19+90.00	77.50 L	GRN/RED					
R47	W/Y	L-861	45	45	RW	21+79.35	47.50 L	WHITE/YELLOW					



MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 ANCHORAGE, AK 99517 (907) 274-2622 CERTIFICATE OF AUTHORIZATION NO. AECC578

'			
	BY	DATE	REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES CENTRAL REGION
4111 AVIATION AVE., ANCHORAGE ALASKA 99502
PHONE (907) 269-0590

KWETHLUK AIRPORT

KWETHLUK, ALASKA

AIRPORT REHABILITATION


PROJECT No. CFAPTO0682

AIP No. 3-02-0435-002-2023

EDGE LIGHT AND HANDHOLE

SCHEDULES

1/4/2023



CERTIFICATE OF AUTHORIZATION

ΒY

DATE


REVISION

NO. AECC578


42 OF 60

4111 AVIATION AVE., ANCHORAGE ALASKA 99502

PHONE (907) 269-0590



CONDUIT CROSSING DETAIL




TRENCH DETAIL


NOTES FOR DETAILS 1 AND 2:

- 1. NUMBER OF CONDUITS PER TRENCH TO BE DETERMINED IN FIELD (2 SHOWN). WIDTH OF TRENCH PER SPECIFICATION I -110.
- 2. INSTALL NEW LIGHT BASES AND CONDUITS PRIOR TO PLACEMENT OF SURFACE COARSE.
- 3. IN AREAS OF NEW CONSTRUCTION, SEE CIVIL FOR SURFACING AND BACKFILL. IN EXISTING AREAS, MATCH EXISTING SURFACE AND BACKFILL.
- 4. SEPARATION BETWEEN CONDUITS SHALL BE AS FOLLOWS. UTILIZE COMMERCIALLY AVAILABLE DUCT SPACERS, 5' O.C., TO MAINTAIN
 - BETWEEN LIGHTING CONDUITS 4" MIN.

 - BETWEEN SYSTEMS OF DIFFERENT VOLTAGES 12" MIN.
 BETWEEN AIRPORT LIGHTING AND FAA CONDUITS 12" MIN.
 BETWEEN FAA POWER AND FAA COMM CONDUITS 6" MIN.
 - BETWEEN FAA POWER CONDUITS 6" MIN.
- 5. MINIMUM BURIAL DEPTH SHALL BE AS FOLLOWS:
 - AIRPORT LIGHTING AND WIND CONE CONDUITS: 18IN
 ALL OTHER CONDUITS: 30IN OR AS INDICATED
- 6. PROVIDE TWO RUNS OF WARNING TAPE AND COUNTERPOISE WIRE IF WIDTH OF CONDUITS IS OVER 36IN WIDE.
- 7. 4" RSC SLEEVE SHALL EXTEND 3' OUTSIDE OF STRUCTURAL


TOE OF EMBANKMENT






DETAIL NOTES:

- 1. CONDUIT SHALL BE INSTALLED WITH CROWN TO DRAIN TO LIGHT BASES AS SHOWN.
- 2. IF 'S' IS LESS THAN 20FT, OR IF 0.25PCT SLOPE CAN BE MAINTAINED IN ONE DIRECTION DUE TO SLOPE OF GRADE, LAY CONDUIT STRAIGHT WITHOUT CROWN BETWEEN BASES/HANDHOLES.





MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 ANCHORAGE, AK 99517 (907) 274-2622 CERTIFICATE OF AUTHORIZATION NO. AECC578

BY DATE **REVISION**

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502


PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION

PROJECT No. CFAPT00682 A1P No. 3-02-0435-002-2023 TRENCH, CONDUIT INSTALLATION, AND COUNTERPOISE DETAILS

43 of 60

1/4/2023




NO. AECC578

BY

DATE

REVISION

MANUFACTURER'S RECOMMENDATION. EACH CRIMP SHALL BE MADE WITH TWO CRIMPS, ROTATED 90DEG.



1/4/2023



-BOND RMC AND POLE TO GROUND CONDUCTOR -BASE COVER POLE -BASE PLATE, SEE LEVELING NUTS LEVELING NUTS SPECIFICATION L-107-3.1 2.5IN 1.25IN ANCHOR BOLTS ANCHOR BOLTS-10'MAX FINISHED GRADE-FINISHED GRADE-HDPE, 2-#10, #10G TO EEB -L867B HANDHOLE. BOND ALL GROUND CONDUCTORS TO INTERNAL LUG 46 BARE CU -3/4INX10' GROUND ROD 2-#10, #10G. IN ZIN CONDUIT

NOTES:

- 1. PROVIDE STRUCTURAL FOUNDATION PER SECTION L-107.
- 2. VERIFY ANCHOR BOLT SIZE, BOLT CIRCLE, AND FOUNDATION SIZE WITH MANUFACTURER'S SHOP DRAWINGS.

PRIMARY WIND CONE FOUNDATION DETAIL

1 PRIMARY WIND CONE FOUNDATION DETAIL

POLE

2.5IN

PROVIDE STRUCTURAL FOUNDATION PER SECTION L-107.

-BOND RMC AND POLE TO GROUND CONDUCTOR

100W, 6.6A/6.6A

2" HDPE, 2-#8, 5KV AIRPORT CABLE, 1-#6 BCU

-L867B HANDHOLE. BOND ALL GROUND CONDUCTORS TO INTERNAL LUG

TO EDGE LIGHT

ISOLATION TRANSFORMER

-3/4INX10' GROUND ROD

2C#14 ARCTIC GRADE SOOW CORD,

1—#6 BCU IN 2IN CONDUIT, OR AS SPECIFIED BY THE WIND CONE MANUFACTURER.

46 BARE CU

-BASE COVER

-BASE PLATE, SEE

SPECIFICATION

L-107-3.1

1.25IN -

VERIFY ANCHOR BOLT SIZE, BOLT CIRCLE, AND FOUNDATION SIZE WITH MANUFACTURER'S SHOP DRAWINGS.

SUPPLEMENTAL WIND CONE FOUNDATION DETAIL

WIND CONE: L-807, SIZE 1, INTERNALLY LIGHTED. PROVIDE WITH MARINE TREATED POWDER COAT FINISH, SS WINCH, SS CABLE, AND SS HARDWARE.

-LED OBSTRUCTION

18IN

INTERNATIONAL ORANGE FABRIC WINDSOCK

-GALVANIZED STEEL POLE PER SPECIFICATION

WIND CONE FRAMEWORK

-POSITION OF FIXTURE LOWERED FOR SERVICING

—INTERNAL LED FLOOD LIGHT

POINT

16 FT

LOCKING DEVICE-

WINCH WITH CABLE-

PRIMARY AND SUPPLEMENTAL WIND CONE DETAIL

45 NTS


MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 **ANCHORAGE, AK 99517** (907) 274-2622 CERTIFICATE OF AUTHORIZATION NO. AECC578

BY DATE REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023 WIND CONE DETAILS

1/4/2023





NO. AECC578

BY


DATE


REVISION






MOUNTING MAINS <u>OPTIONS</u> PANEL: B PROJECT: KWETHLUK AIRPORT 1. SOLID NEUTRAL SURFACE LUGS 2. GROUND BAR LOCATION: EEB VOLTAGE: 240/120 VOLT 1 PHASE 3 WIRE 100 A MLO 22k AIC CIRCUIT DESCRIPTION AMP CIRCUIT DESCRIPTION KVA CKT CKT AMP Р KVA LIGHTING CONTROL PANEL 0.6 20 20 ENCLOSURE LIGHTS 1 2 1 0.4 ROTATING BEACON & MOTOR 20 CONV. RECEPTS 0.4 3 4 20 0.4 BEACON STRIP HEATER AND 0.4 20 5 6 RECEPTACLE 20 2 2.0 ELECTRIC HEAT WIND CONE (PRIMARY) 0.1 20 8 CONTROL PANEL STRIP HEATER 10 9 20 0.1 4 kW REGULATOR (RW AND TW) 4.9 30 11 12 20 SPARE RADIO CONTROLLER 20 13 14 20 **SPARE** 15 SPARE 20 16 20 **SPARE** 17 SPACE SPARE 20 18 SPACE 19 20 SPACE SPACE 21 SPACE 22 SPACE 23 24 SPACE SPACE 25 26 SPACE SPACE SPACE 27 28 SPARE 29 SPACE 30 20 CONNECTED LOAD: 9.4 KVA 39.2 Α DEMAND LOAD: 11.2 KVA 46.8








STATE OF ALASKA **AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023 EEB ONE-LINE DIAGRAM, GROUNDING DETAIL, AND PANEL SCHEDULE

EQUIPMENT LIST ITEM # (TYP.)

1/4/2023 49 of 60




PE CONTROL TO BE MOUNTED 24 IN ABOVE ENCL. ROOF ORIENTED NORTH


NOTE: SEE SHEET 48 FOR EQUIPMENT LIST.

DEPARTMENT OF TRANSPORTATION

DATE:

RFV:





LIGHTING CONTROL PANEL ELEVATION

CONTROL DIAGRAM LEGEND

- TERMINAL BLOCK 20A, 12 POINT, NO. AS REQUIRED GE CR151B2 OR APPROVED EQUAL
- → FIELD WIRING
- RELAY COIL 3PDT RELAY, PLUG—IN TYPE WITH BASE
- RELAY COIL TIME DELAY RELAY, OFF DELAY, DPDT, SET AT 15 MINUTES
- NORMALLY OPEN CONTACT, "X" = COIL
- NORMALLY CLOSED CONTACT, "X" = COIL
- . SELECTOR SWITCH, PANEL MOUNT, NUMBER OF POSITIONS AS INDICATED
- TWO POSITION: C-H 10250T20LB THREE POSITION: C-H 10250T21LB OR APPROVED EQUAL

IDEC RR5PAU-AC120V

OR APPROVED EQUAL

OR APPROVED EQUAL

C-H 10250T197LGP2A

OR APPROVED EQUAL

GE CR2943AJ301B

OR APPROVED EQUAL

MAGNACRAFT TDRSRXP-120V

- XA FUSE HOLDER WITH SLO-BLO FUSE, "X" = FUSE RATED AMPS
- PILOT LIGHT, PANEL MOUNT, LED, 120V, GREEN COLOR, 30mm
- AIRFIELD LIGHTING EQUIPMENT "X", SEE SHEET 34 $\langle x \rangle$
- PUSH BUTTON STATION. OFF-ON MOMENTARY CONTACT, WATER-DUST TIGHT, NEMA 4X
- WEATHERPROOF GFCI RECEPTACLE

CONTROL SEQUENCE DESCRIPTION

RUNWAY AND TAXIWAY LIGHTS

ON-LIGHTS ON AT PRESET BRIGHTNESS.

OFF-LIGHTS OFF.

AUTO-EXTERIOR PUSH BUTTON SWITCH WILL TURN ON RUNWAY AND TAXIWAY LIGHTS FOR 15 MINUTES (ADJUSTABLE) AT PRESET BRIGHTNESS.

RADIO CONTROL ENABLED

- 3 CLICKS OF MIC TURNS ON RW/TW LIGHTS AT STEP 1. 5 CLICKS OF MIC TURNS ON RW/TW LIGHTS AT STEP 2.
- 7 CLICKS OF MIC TURNS ON RW/TW LIGHTS AT STEP 3.
- LIGHTS REMAIN ON FOR 15 MINUTES AFTER LAST CLICK.

IF PUSHBUTTON CONTROL AND RADIO CONTROL ARE BOTH ACTIVE RADIO CONTROL HAS PRIORITY.

SUPPLEMENTAL WINDCONE

WINDCONE LIGHTS ON WHEN RUNWAY AND TAXIWAY LIGHTS ARE ON.

ROTATING BEACON AND PRIMARY WINDCONE

ON-BEACON AND WINDCONE ON.

OFF-BEACON AND WINDCONE OFF.

AUTO- PHOTOELECTRIC CONTROL IS ENABLED. BEACON AND WINDCONE ARE ON FROM DUSK TO DAWN.

BEACON OUTLET AND HEATER ARE ON WITH SWITCH IN ANY POSITION.

MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 ANCHORAGE, AK 99517 (907) 274-2622 CERTIFICATE OF AUTHORIZATION NO. AECC578 ΒY DATE **REVISION**


STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502


PHONE (907) 269-0590


KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION


PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023 AIRFIELD LIGHTING CONTROL DIAGRAM


1/4/2023 50 of 60














ŀ	KWETHLUK A	IRPORT FAA PAF	PI/REIL HANDHOL	E SCHEDULE
NO.	SYSTEM	PAY ITEM	LOCATION	COVER LEGEND
F1	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F2	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F3	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F4	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F5	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F6	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F7	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F8	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F9	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F10	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F11	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F12	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F13	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F14	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F15	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F16	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F17	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F18	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F19	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F20	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F21	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F22	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F23	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F24	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F25	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL POWER
F26	PAPI/REIL	L132.010.0010	FIELD LOCATE	PAPI/REIL COMM
F27	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL POWER
F28	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL COMM
F29	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL POWER
F30	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL COMM
F31	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL POWER
F32	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL COMM
F33	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL POWER
F34	PAPI/REIL	L132.010.0020	FIELD LOCATE	PAPI/REIL COMM


GUARD WIRE NOTES:

- ALL CONNECTIONS TO GUARD WIRE AND GROUND RODS TO BE ACHIEVED BY EXOTHERMIC WELDS.
- 2. GUARD WIRE SHALL RUN CONTINUOUSLY ALONG DUCT RUN WITH NO DEVIATIONS FROM THE RUN OF DUCT AND WITH NO GAPS.
- 3. SPACING BETWEEN GROUND RODS ALONG A DUCT BANK SHALL
- 4. GROUND RODS SHALL BE INSTALLED APPROXIMATELY 6' FROM DUCT ON ALTERNATING SIDES OF THE TRENCH AND CONNECT TO GUARD WIRE AS SHOWN IN DETAILS. MAINTAIN A MINIMUM 9" BEND RADIUS IN JUMPER WIRE SWEEPS.











MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 ANCHORAGE, AK 99517 (907) 274-2622 CERTIFICATE OF AUTHORIZATION NO. AECC578 BY DATE REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023 FAA GUARD WIRE DETAILS AND HANDHOLE SCHEDULE

1/4/2023 56 of 60






TRENCH NOTES:

- 1. WIDTH OF TRENCH AND NUMBER OF CONDUITS PER TRENCH TO BE DETERMINED IN FIELD.
- 2. IN AREAS OF NEW CONSTRUCTION, SEE CIVIL FOR SURFACING AND BACKFILL. IN EXISTING AREAS, MATCH EXISTING SURFACING AND BACKFILL.
- 3. BEDDING MATERIAL PER SECTION L-110-3.3.
- SEPARATION BETWEEN CONDUITS SHALL BE AS FOLLOWS. UTILIZE COMMERCIALLY AVAILABLE DUCT SPACERS, 5' O.C., TO MAINTAIN
 - BETWEEN AIRPORT LIGHTING AND FAA CONDUITS 12" MIN.
 BETWEEN FAA POWER AND FAA COMM CONDUITS 6" MIN.
 BETWEEN FAA POWER CONDUITS 6" MIN.
- 5. PLOWING OF CONDUITS WILL NOT BE ALLOWED.
- 6. INSTALL CONDUITS TO DRAIN TO HANDHOLES.
- PROVIDE TWO RUNS OF GUARD WIRE AND WARNING TAPE FOR TRENCHES OVER $36^{\prime\prime}$ WIDE.
- 8. INSTALL CONDUIT PER SECTION L-110 UNLESS NOTED OTHERWISE.
- 3/4IN X 10 FT GROUND ROD PLACED 6 FT FROM TRENCH AT APPROXIMATE 90FT INTERVALS, VARY SPACING 10-20% TO PREVENT RESONANCE. SEE DETAIL 1/54. THE JUMPER WIRES SHALL BE SWEPT AWAY FROM THE GUARD WIRE IN A REPEATABLE PATTERN SUCH THAT A LIGHTNING IMPULSE WILL ALWAYS BE ABLE TO FOLLOW A CURVED PATH TO GROUND WITHIN 180 FT. OF ANY POINT ALONG THE RUN. MAINTAIN A MINIMUM 9IN. RADIUS BEND IN THE JUMPER SWEEPS. PROVIDE TWO GUARD WIRES WHEN WIDTH OF DUCTS EXCEEDS 3 FT. PROVIDE 12" MINIMUM BETWEEN GUARD WIRES. EACH GUARD WIRE SHALL BE 12IN-18IN INSIDE THE OUTERMOST EDGES OF




MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 ANCHORAGE, AK 99517 (907) 274-2622 CERTIFICATE OF AUTHORIZATION NO. AECC578





STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023 FAA TRENCH DETAILS

1/4/2023







REIL INSTALLATION NOTES:

- 1. ALL EQUIPMENT INSIDE THE PAPI/REIL SHELTER, INCLUDING THE MAIN CONTROL CABINET AND A/G RECEIVER, IS ETR. THE IINDIVIDUAL CONTROL CABINETS AND IDENTIFIERS (REIL HEADS) ARE ETR. ALL OTHER EQUIPMENT, CONDUIT, CONDUCTORS, AND MATERIALS ARE NEW, PROVIDED BY CONTRACTOR.
- 2. INSTALL A #2 XHHW-2 GREEN GND WIRE FROM THE GROUND LUG IN EACH CABINET. CONNECT TO EES WITH EXOTHERMIC WELD.
- GROUND FLASHER HEADS WITH A #12 GREEN INSULATED COPPER WIRE. ROUTE THE WIRE THROUGH THE FLEXIBLE CONDUIT AND ATTACH IT TO THE GROUND CLAMP INSIDE THE INDIVIDUAL CONTROL CABINETS.
- 4. CONDUITS SHALL ENTER THROUGH EXISTING PENETRATIONS IN THE BOTTOM OF THE CABINETS.
- 5. A WATERTIGHT SEALANT SHALL BE APPLIED AT CONDUIT—TO—CABINET FITTINGS.
- THE IDENTIFIERS SHALL BE AIMED 15 DEGREES OUTWARD FROM THE RUNWAY CENTERLINE AND 10 DEGREES ABOVE THE HORIZONTAL.
- 7. INSTALL A GROUNDING BUSHING AT BOTH ENDS OF ALL CONDUITS IN ALL CABINETS.
- 8. ALL SPLICES SHALL OCCUR INSIDE THE REIL ICC #1 USING TERMINAL STRIP 2TB1, FOLD BACK, SECURE, AND TAPE ALL UNUSED #19 CONDUCTORS.
- 9. THE ELEVATION OF BOTH LAMP HEADS SHALL BE WITHIN 3 FEET OF A HORIZONTAL PLANE THROUGH THE RUNWAY CENTERLINE, OR A MAXIMUM OF 5 FEET ABOVE THE SURROUNDING GRADE. FIELD MEASURE AND INSTALL AT HIGHEST ACCEPTABLE FI FVATION



MBA CONSULTING ENGINEERS, INC.
3812 SPENARD ROAD, SUITE 200
ANCHORAGE, AK 99517
(907) 274-2622
CERTIFICATE OF AUTHORIZATION
NO. AECC578

BY DATE REVISION

STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION
4111 AVIATION AVE., ANCHORAGE ALASKA 99502
PHONE (907) 269-0590

KWETHLUK AIRPORT
KWETHLUK, ALASKA
AIRPORT REHABILITATION
PROJECT NO. CFAPTO0682
AIP No. 3-02-0435-002-2023
REIL WIRING SCHEMATIC

1/4/2023

ELECTRIC UTILITY GENERAL NOTES:

- 1. COORDINATE ALL WORK WITH THE LOCAL UTILITY COMPANY.
- 2. COORDINATE ALL OUTAGES WITH THE FAA THROUGH THE ENGINEER.
- 3. VERIFY STATUS OF ALL EXISTING SYSTEMS PRIOR TO THE START OF POWER LINE WORK.
- 4. LOCATE UNDERGROUND UTILITIES AT ALL POLE AND ANCHOR LOCATIONS PRIOR TO EXCAVATION.
- ALL WORK SHALL COMPLY WITH THE LATEST EDITIONS OF ANSI C2-NESC, NFPA 70-NEC, RUS BULLETIN 1728F-804 SPECIFICATIONS AND DRAWINGS FOR 12.47/7.2 kV OVERHEAD DISTRIBUTION SYSTEMS, INCLUDING ANY STATE OF ALASKA AMENDMENTS, AND LOCAL UTILITY REQUIREMENTS.
- 6. SOIL CONDITIONS AT POLE AND GUY ANCHOR LOCATIONS HAVE NOT BEEN VERIFIED. PRELIMINARY INFORMATION INDICATES THAT CLASS 7 OR CLASS 8 SOILS (RUS BULLETIN 1728F-804, SECTION F) ARE LIKELY TO BE ENCOUNTERED. VERIFY SOIL HOLDING POWER AT POLE AND ANCHOR LOCATIONS PRIOR TO START OF WORK. PROVIDE POLE EMBEDMENT AND GUY ANCHORING AS REQUIRED FOR SOIL TYPES.
- 7. SEE SREB DRAWINGS FOR SECONDARY SERVICE DETAILS.
- 8. SEE SHEET UE6 FOR STAKING SHEET.

ELECTRIC UTILITY SHEET NOTES:

- PROVIDE TEMPORARY POWER TO THE AIRFIELD LIGHTING EQUIPMENT (EEB) USING A TEMPORARY GENERATOR. EXPECT APPROXIMATELY 15 KW LOAD, 120/240V, SINGLE PHASE. THE EXISTING EEB HAS A 100A GENERATOR INLET AND TRANSFER SWITCH. TEMPORARY POWER SHALL BE AVAILABLE 24/7 EXCEPT DURING SCHEDULED OUTAGES. CONTRACTOR TO COORDINATE OUTAGES THROUGH THE ENGINEER.
- DISCONNECT AND REMOVE EXISTING SECONDARY CONDUCTORS TO THE SREB METER, EEB METER, AND THE METER SERVING THE FAA PAPI/REIL SHELTER AND AWOS.
- DISCONNECT AND REMOVE EXISTING PRIMARY CONDUCTORS BACK TO NEXT POLE, COIL AND PROTECT FOR RE-INSTALLATION.
- (4) DISCONNECT AND REMOVE EXISTING TRANSFORMER AND APPURTENANCES.
- 5 REMOVE EXISTING POWER POLE, GUYS, ANCHORS, CUTOUTS, ATTACHMENTS, AND APPURTENANCES.
- PROVIDE NEW 45' POWER POLE IN EXISTING LOCATION, INSTALL TRUE AND PLUMB. PROVIDE GUYS AS SHOWN. PROVIDE NEW TRANSFORMER, CUTOUTS, SURGE ARRESTOR (MOUNTED ON TRANSFORMER), MOUNTING HARDWARE, AND APPURTENANCES AS SHOWN AND AS SPECIFIED. POLE SHALL BE SET SUCH THAT IT LEANS AWAY FROM THE STRAIN OF THE PRIMARY CONDUCTORS. IT SHALL BE SET SUCH THAT THE FINAL RAKE IS NOT LESS THAN 1 INCH FOR EACH 10 FEET OF POLE HEIGHT ABOVE GROUND AFTER THE CONDUCTORS ARE INSTALLED AT THE REQUIRED TENSION.
- (7) RECONNECT EXISTING PRIMARY CONDUCTORS TO NEW CUTOUTS.
- PROVIDE NEW SERVICE CONDUCTORS TO THE METER AT THE FAA PAPI/REIL SHELTER AND TO THE METER ON THE NEW SREB. OVERHEAD TO EXISTING POLE P-0, THEN UNDERGROUND TO NEW SREB METER, SEE SHEETS 38, E2, AND E6. EXISTING FAA METER IS MOUNTED ON POLE P-0. ATTACH TO POLE P-0 AT 21 FEET ABOVE GRADE TO MAINTAIN 20 FEET MINIMUM ABOVE THE ACCESS ROAD.
- PROVIDE NEW CUTOUTS TO DISCONNECT THE PRIMARY LINE FEEDING THE AIRPORT.
 PRIMARY TO BE DISCONNECTED WHILE POLE P-1 IS BEING REPLACED AND WHILE WORK IS BEING PERFORMED AT CULVERTS ALONG THE ACCESS ROAD.

ELECTRIC UTILITY LEGEND:

- --- EXISTING POWER POLE
- -D- NEW POWER POLE
- **P**OLE GROUNDING ELECTRODE

→ DOWN GUY AND ANCHOR→ X TRANSFORMER; X = kVA

P-X POLE DESIGNATION

- OHE-

UGE-

MEW MULTI-METER BASE

OHE — EXISTING OVERHEAD ELECTRIC LINE

UGE—— EXISTING UNDERGROUND ELECTRIC LINE

NEW OVERHEAD ELECTRIC LINE

NEW UNDERGROUND ELECTRIC LINE

EXISTING ROAD SIGN

ELECTRIC UTILITY ABBREVIATIONS:

ANSI AMERICAN NATIONAL STANDARDS INSTITUTE

AWOS AUTOMATED WEATHER OBSERVING SYSTEM

BIL BASIC IMPULSE LEVEL

BS BACK SPAN

CB CIRCUIT BREAKER

EEB ELECTRICAL EQUIPMENT BUILDING

ETR EXISTING TO REMAIN

EX EXISTING

FT FEET

LT LEFT

MISC MISCELLANEOUS

NEC NATIONAL ELECTRICAL CODE

NESC NATIONAL ELECTRICAL SAFETY CODE

NFPA NATIONAL FIRE PROTECTION ASSOCIATION

NFS NON-FROST SUSCEPTIBLE SOIL

NO NUMBER

OHE OVERHEAD ELECTRIC

RT RIGH

RUS RURAL UTILITIES SERVICE

SREB SNOW REMOVAL EQUIPMENT BUILDING

SZ SIZE

TYP TYPICAL

UGE UNDERGROUND ELECTRIC

XFMR TRANSFORMER



MBA CONSULTING ENGINEERS, INC.
3812 SPENARD ROAD, SUITE 200
ANCHORAGE, AK 99517
(907) 274-2622
CERTIFICATE OF AUTHORIZATION
NO. AECC578

BY DATE REVISION

STATE OF ALASKA DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION


4111 AVIATION AVE., ANCHORAGE ALASKA 99502


PHONE (907) 269-0590


KWETHLUK AIRPORT
KWETHLUK, ALASKA
AIRPORT REHABILITATION
PROJECT No. CFAPT00682
AIP No. 3-02-0435-002-2023
UTILITY LEGEND AND NOTES


1/4/2023

UE1 of UE6









	H
ed By	ć
Design	-
]	_

93

Date Revised: 1/ Layout Name: UE

					CONDU	JCTOR						DD	IMADV	١,	GUYS	ΔN	CHORS	YEC	DRMERS	SEC	ONDARY	SF.	RVICE		MISC		
EXIST/	NFW			SERVICE		SECONDARY		PRIMARY		LOCATION	HEIGHT &	PRIMARY ASSEMBLY				(F) (G)		(J)		(K)		(M)		REMARKS			
LAISTA		NO.	SZ.			BACK		SZ.	DACK	LOOKHON																KEWAKKS	
		T	YPE	SPAN	TYPE	SPAN	T	YPE	SPAN			NO.	UNITS	NO.	UNITS	NO.	UNITS	NO.	UNITS	NO.	UNITS	NO.	UNITS	NO.	UNITS		
							2	#2	070			1	A5.1	2	E1.1L	2	F6.10	1	G1.6	1	J3.1			1	H1.1	75 KVA XFMR (NOTE 8), FUSED	
NEW POLE		•		1			AC	CSR	232	LOCATION OF		1	N5.2											1	W1.1G	CUTOUT W/40A FUSE (NOTE 6), SURGE ARRESTOR (NOTE 7). SERVICE CONDUCTOR TO BE	
P-1										EXISTING	45-4															SERVICE CONDUCTOR TO BE	
				1						POLE																90C XHHW—2 TRIPLEX CONDUCTOR. (NOTE 10)	
							2	#2		BEGINNING		1	A6.1											1	S1.1	NEW PRIMARY CUTOUT	
EXISTING							A	CSR		OF ACCESS																	
POLE P-2										ROAD NEAR																	
										SCHOOL																	
		1	750KCM	110											1	E1.1	1	F3.12			1	J3.1			1	H1.1	NEW GUY AND ANCHOR
EXISTING SERVICE		TRI	IPLEX	110						ON APRON NEAR FAA																	
POLE P-0										SHELTER																	
				1														<u> </u>									
				1																							
										\																	

NOTES

- 1. #2 ACSR SHALL BE CODE WORD SPARATE, 7/1 AL/STL STR.
- 2. GROUND WIRES AT POLES SHALL BE #4 BARE CU.
- 3. INSTALL NEUTRAL ON LOAD SIDE.
- 4. JUMPER WITH #2 ACSR AND COMPRESSION CONNECTOR.
- 5. UNIT DESIGNATION ON STAKING SHEETS REFER TO RUS BULLETIN 1728F-804 DRAWING NUMBERS. REFERENCED DRAWINGS ARE IN PROJECT SPECIFICATIONS APPENDIX 0.
- 6. FUSED CUTOUT: 15KV, 95KV BIL, 200A, 10KA, TYP T FUSE.
- 7. SURGE ARRESTER.: DISTRIBUTION CLASS, 9KV.
- 8. TRANSFORMER: 75KVA, SINGLE PHASE, 7200V PRIMARY, 120/240V 3-WIRE SECONDARY, 95KV BIL. PROVIDE PRIMARY FUSES PER NEC AND MANUFACTURER'S RECOMMENDATIONS, PROVIDE 400A 2P SECONDARY CB.
- 9. LINE INSULATORS: 95KV BIL MINIMUM.
- 10. PROVIDE NUMBER OF GUY AND ANCHOR UNITS AS NEEDED FOR REQUIRED HOLDING POWER IN SOIL ENCOUNTERED AT POLE LOCATION.



MBA CONSULTING ENGINEERS, INC.
3812 SPENARD ROAD, SUITE 200
ANCHORAGE, AK 99517
(907) 274-2622
CERTIFICATE OF AUTHORIZATION
NO. AECC578

				l
•				
	BY	DATE	REVISION	
				_


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION
4111 AVIATION AVE., ANCHORAGE ALASKA 99502


PHONE (907) 269-0590

KWETHLUK AIRPORT
KWETHLUK, ALASKA
AIRPORT REHABILITATION
PROJECT No. CFAPT00682
AIP No. 3-02-0435-002-2023
UTILITY STAKING SHEET

1/4/2023

UE6 of UE6





| Date Revised: 1/05/2023, 1:3. | Layout Name: 0vw | File Path and Name: | \rm.rmnet\z\c

	CONSTRUCTION	PHASE 7	TABLE		
CONSTRUCTION PHASE	WORK TO BE COMPLETED	DURATION	RUNWAY CLOSURE	TAXIWAY CLOSURE	COMPLETION
PHASE 1	CONSTRUCT AND SURCHARGE SUPPLEMENTAL WIND CONE ACCESS ROAD EMBANKMENT	30 DAYS	NIGHTLY RUNWAY CLOSURE 7PM — 9AM	NONE	2023
PHASE 2	REESTABLISH EMBANKMENT GRADES FOR FUTURE HALF—WIDTH OPERATIONS. DEMO OF EXISTING AIRFIELD LIGHTING AND NAVAIDS	25 DAYS	NIGHTLY RUNWAY CLOSURE 7PM — 9AM	NONE	2024
PHASE 3	CONSTRUCT WEST HALF OF RUNWAY, WEST HALF OF RUNWAY LIGHTING, NORTH HALF OF APRON, AIRCRAFT TIE—DOWNS, SREB FACILITIES, & WEST HALF OF FAA NAVAIDS	40 DAYS	HALF-WIDTH DAY OPERATIONS. NIGHTLY CLOSURE 7PM — 9AM	NONE	2024
PHASE 4	CONSTRUCT EAST HALF OF RUNWAY, EAST HALF OF RUNWAY LIGHTING, TAXIWAY, TAXIWAY LIGHTING, SOUTH HALF OF APRON, SEGMENTED CIRCLE, PRIMARY WIND CONE, SUPPLEMENTAL WIND CONE, & EAST HALF OF FAA NAVAIDS	40 DAYS	HALF-WIDTH DAY OPERATIONS. NIGHTLY CLOSURE 7PM — 9AM	NIGHTLY CLOSURE 7PM — 9AM	2024
PHASE 5	CONSTRUCT ACCESS ROAD, REPLACE CULVERTS, & INSTALL SIGNS	45 DAYS	NONE	NONE	2024

-ROTATING BEACON

PHASE PHASE ✓ WEATHER STATION

AREA

-TAXIWA

STAGING/STOCKPILE

-PRIMARY WIND CONE AND

SEGMENTED CIRCLE


RUNWAY SAFETY AREAS RUNWAY RW 18-36 TEMPORARY RW EXISTING / PHASE 5 | PHASE 1 / PHASE 2 PHASE 3 PHASE 4 RUNWAY DESIGN CODE A-I(S)-5000A-I(S)-5000A-I(S)-5000A-I(S)-5000APPROACH TYPE VIS VIS VIS VIS RUNWAY TYPE UTILITY UTILITY UTILITY UTILITY 35' x 3,199 35' x 3.199 RUNWAY DIMENSIONS 75' x 3,199 35' x 3,199 60' x 3,679 RUNWAY SAFETY AREA 120' x 3,679 60' x 3,679 RUNWAY OBJECT FREE AREA 250' x 3.679 250' x 3,679 125' x 3,679 UNWAY OBSTACLE FREE ZONE 125' x 3,599 250' x 450' x 1,000 PRIMARY SURFACE WIDTH 250

				TAXIV	VAY SAFETY	AREAS				
	TAXIWAY	WIE	HTC	SHOU	JLDER	TS	SA	TOFA		
1	IAAIWAI	STANDARD	TEMPORARY	STANDARD	TEMPORARY	STANDARD	TEMPORARY	STANDARD	TEMPORARY	
	TAXIWAY	25'	25'	10'	10'	49'	49'	89'	89'	

SAFETY AREA TABLE NOTES:

 DIMENSIONS REDUCED FROM FAA AC 150/5300-13B STANDARDS. RSA, ROFA, AND OFZ ARE CENTERED ABOUT PERMANENT/TEMPORARY RUNWAY CENTERLINE.

2. ADDITIONAL SAFETY AREA DIMENSIONS, INCLUDING LENGTHS BEYOND RUNWAY ENDS, TSA, AND TOFA DIMENSIONS ARE AVAILABLE IN THE CSPP NARRATIVE.



GENERAL SAFETY REQUIREMENTS:

0

SEE APPENDIX C OF THE SPECIFICATIONS FOR THE CONSTRUCTION SAFETY AND PHASING PLAN (CSPP)
REQUIREMENTS. THE CONTRACTOR SHALL COMPLY WITH THE SAFETY REQUIREMENTS AS REQUIRED IN THE
CSPP. ALL SAFETY RELATED WORK SHALL BE SUBSIDIARY TO THE CONTRACT AND NO ADDITIONAL
PAYMENT WILL BE MADE.

ACCESS

ROAD

SREE

PHASE

APR0

- 2. THE CONTRACTOR SHALL SUBMIT A SAFETY PLAN COMPLIANCE DOCUMENT, PER FAA AC 150/5370-2, TO THE ENGINEER FOR REVIEW AND APPROVAL PRIOR TO ISSUANCE OF A NOTICE TO PROCEED. IF THE CONSTRUCTION PHASING PLAN DIFFERS FROM WHAT IS SHOWN OR IF SUBSEQUENT CHANGES ARE MADE, SUBMIT A REVISION TO THE ENGINEER FOR REVIEW AND APPROVAL.
- 3. DURING PHASES 1, 2, 3, AND 4, THE CLOSED PORTIONS OF THE RUNWAY AND TAXIWAY MAY BE USED AS A HAUL ROUTE. HAUL ROUTES WILL NOT BE ALLOWED ON ANY OPEN RUNWAY OR TAXIWAY, INCLUDING THE ACTIVE RSA OR TSA.
- 4. WHEN WORKING NEAR THE OPEN RUNWAY, EVACUATE ALL PERSONNEL AND EQUIPMENT TO THE SAFE ZONES DESCRIBED IN DETAILS 1 AND 2 ON SHEET ACG, 15 MINUTES PRIOR TO AND 15 MINUTES AFTER ALL ARRIVALS AND DEPARTURES. WHEN PERSONNEL AND EQUIPMENT CANNOT BE EVACUATED TO THE SAFE ZONES, THEY MUST EVACUATE THE RUNWAY SAFETY AREA (RSA) AND/OR TAXIWAY SAFETY AREA (TSA) AND MOVE AS FAR AWAY FROM THE RUNWAY CENTERLINE AS PRACTICAL DURING AIRCRAFT OPERATIONS. IN NO CASE CAN PERSONNEL OR EQUIPMENT BE INSIDE THE RSA OR TSA DURING AIRCRAFT OPERATIONS.
- 5. DETERMINE THE TIMES OF SCHEDULED FLIGHTS INTO KWETHLUK AIRPORT AND ALLOW AIRCRAFT TO USE THE RUNWAY DURING THE SCHEDULED TIMES. ADJUST START AND STOP TIMES TO ACCOMMODATE THE COMMERCIAL SERVICE SCHEDULE, AS APPROVED BY THE ENGINEER. THE CONTRACTOR SHALL MONITOR THE COMMON TRAFFIC ADVISORY FREQUENCY (CTAF) AND PERFORM VISUAL MONITORING FOR UNSCHEDULED FLIGHTS. THE CONTRACTOR SHALL CLEAR THE RUNWAY ACCORDING TO NOTE 4 FOR ALL ARRIVALS AND DEPARTURES INCLUDING EMERGENCY MEDEVACS. THE CONTRACTOR SHALL BE AWARE OF AND ACCOMMODATE ALL SCHEDULED, UNSCHEDULED, AND CHARTERED OPERATIONS.
- 5. ALL CONSTRUCTION VEHICLES AND EQUIPMENT SHALL OPERATE A FLASHING YELLOW BEACON AND 3' X 3' CHECKERED FLAG WITH 1' X 1' ORANGE AND WHITE SQUARES WHEN WORKING ON THE AIRPORT. THE CONTRACTOR'S SAFETY OFFICER VEHICLE SHALL HAVE BOTH A YELLOW FLASHING BEACON AND A SEPARATE VISUAL AND/OR AUDIBLE SIGNAL (E.G., COLORED FLASHING BEACON OTHER THAN YELLOW, MEGAPHONE, AIR HORN, 2—WAY RADIO CONTACT, ETC) USED TO SIGNAL WORKERS TO CLEAR THE AREAS DESCRIBED IN NOTE 4 DURING AIRCRAFT TAKEOFFS AND LANDINGS.
- 7. KEEP AREAS WITHIN THE RUNWAY OBJECT FREE AREA (ROFA) AND ACTIVE TAXIWAY SAFETY AREA (TSA) LIMITS CLEAR OF CONSTRUCTION MATERIALS. REMOVE ANY DEBRIS FROM THESE AREAS WITHIN 15 MINUTES OF VERBAL NOTICE FROM THE ENGINEER OR ENGINEER'S REPRESENTATIVE.

3. CLEAR SAFETY AREAS AND OBJECT FREE AREAS AT ANY TIME DIRECTED BY THE ENGINEER.

AIRPORT PROPERTY BOUNDARY

WEATHER STATION CRITICAL AREA,

-PHASE

R = 500'

RUNWAY 18-36±

- 9. DAMAGE TO FAA FACILITIES INCLUDING POWER DISRUPTION SHALL BE IMMEDIATELY REPAIRED IN A MANNER ACCEPTABLE TO THE FAA AT THE CONTRACTOR'S EXPENSE.
- 10. REMOVE MATERIAL STOCKPILES AND EQUIPMENT FROM OBJECT FREE AREAS DURING NON-WORK HOURS.
- 11. PROVIDE AIRPORT FLAGGERS FOR ALL OPEN TAXIWAYS AND RUNWAYS DURING ACTIVE CONSTRUCTION OPERATIONS IN THE RUNWAY, TAXIWAY, APRON, RSA, OR TSA AND WHERE THE ENGINEER DETERMINES A FLAGGER IS NECESSARY.
- 12. CONTRACTOR HAULING OPERATIONS ARE SHOWN ON THE PLANS. FOLLOWING CONSTRUCTION COMPLETION, THE CONTRACTOR IS REQUIRED TO RESTORE THE HAUL ROUTE TO ITS ORIGINAL CONDITION. TEMPORARY ACCESS ROUTES MUST BE REMOVED, AND THE GROUND RESTORED TO ITS ORIGINAL CONDITION.
- 13. THE CONTRACTOR MUST REPORT ANY SAFETY ISSUES TO THE ENGINEER UPON DISCOVERY. THE CONTRACTOR MUST TAKE IMMEDIATE ACTION TO RESOLVE SAFETY ISSUES.
- 14. IMMEDIATELY REMOVE ALL FOREIGN OBJECT DEBRIS (FOD) FROM ACTIVE SURFACES UPON DISCOVERY OR NOTIFICATION. FAILURE TO REMOVE FOD MAY BE CONSIDERED A SAFETY VIOLATION AS DETERMINED BY THE ENGINEER. STATION ADEQUATE CLEANING EQUIPMENT AT THE JOB SITE FOR IMMEDIATE CLEANUP OF ANY MATERIAL SPILLS ON ALL ACTIVE RUNWAY, TAXIWAY, AND APRON SURFACES.
- 15. THE NEW ROTATING BEACON MUST BE OPERATIONAL BEFORE DECOMMISSIONING THE OLD ROTATING BEACON.
- 16. MAINTAIN ACCESS FROM THE AIRPORT TO THE CITY OF KWETHLUK DURING ALL PHASES OF WORK, INCLUDING ACCESS ROAD REHABILITATION AND CULVERT REPLACEMENT. SEE SPECIFICATION G-710.
- 17. PROVIDE HIGHWAY FLAGGERS ALONG THE ACCESS ROAD DURING CULVERT WORK TO MAINTAIN ACCESS TO THE APRON. HIGHWAY FLAGGERS SHALL BE PROVIDED ALONG THE HAUL ROUTES AS REQUIRED BY THE ENGINEER. HAUL ROUTE SHALL BE APPROVED BY THE ENGINEER.

RUNWAY STATUS CHANGE PROCEDURES:

THE CONTRACTOR SHALL NOTIFY FAA (THROUGH THE ENGINEER) AT LEAST 45 DAYS PRIOR TO RUNWAY CLOSURES (PARTIAL OR FULL), RE-OPENING A CLOSED RUNWAY, INTERRUPTING FAA FACILITY SERVICE OR REMOVING AND DISPLACING A RUNWAY THRESHOLD BY EMAILING AN "AIRPORT SPONSOR STRATEGIC EVENT SUBMISSION FORM", FAA FORM 6000-26 TO 9-AJV-SEC-WSA@FAA.GOV.

FOLLOW THESE PROCEDURES ANY TIME THE STATUS OF THE RUNWAY OR TAXIWAY IS TO BE ALTERED.


- CONTRACTOR NOTIFIES ENGINEER OF UPCOMING CHANGE IN AIRPORT STATUS. PROVIDE 5 DAYS ADVANCE NOTICE.
- 2. AIRPORT MANAGER FILES NOTAM WITH FAA.
- 3. CONTRACTOR RECEIVES TENTATIVE APPROVAL TO CHANGE RUNWAY STATUS AT A SPECIFIC TIME AND DATE.
- ON THE DAY OF THE CHANGE IN STATUS, A MEETING IS CONDUCTED WITH ENGINEER TO REVIEW SCHEDULE AND SAFETY PROCEDURES.
- 5. ENGINEER CLOSES RUNWAY/TAXIWAY TEMPORARILY FOR REQUIRED GRADING AND/OR NEW TEMPORARY MARKINGS.
- 6. CONTRACTOR TO GRADE TEMPORARY RUNWAY SO TRANSVERSE GRADES WITHIN TEMPORARY RUNWAY SHALL BE 1-2%. TRANSVERSE GRADES WITHIN TEMPORARY RSA SHALL NOT EXCEED 5%. LONGITUDINAL GRADES ALONG TEMPORARY RUNWAY SHALL NOT EXCEED 2%.
- 7. CONTRACTOR INSTALLS APPROVED TEMPORARY MARKINGS AND/OR APPROVED TEMPORARY LIGHTING.
- 8. ENGINEER INSPECTS AND APPROVES MARKINGS AND LIGHTING.
- 9. CONTRACTOR IS PROVIDED NOTICE TO PROCEED WITH THE WORK
- 10. CONTRACTOR CHANGES RUNWAY STATUS TO A NEW CONFIGURATION, OR CHANGES TO PERMANENT STATUS. AIRPORT MANAGER SHALL CANCEL OR REVISE NOTAM WITH FAA WHEN WORK IS COMPLETE.


PLANS DEVELOPED BY:
R&M CONSULTANTS, INC.
9101 VANGUARD DR.
ANCHORAGE, AK 99507
(907) 522-1707
CERT. OF AUTH. NO. AECC1111
BY DATE REVISION


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION
4111 AVIATION AVE., ANCHORAGE ALASKA 99502
PHONE (907) 269-0590


KWETHLUK AIRPORT
KWETHLUK, ALASKA
AIRPORT REHABILITATION
PROJECT No. CFAPT00682
AIP No. 3-02-0435-002-2023
CONSTRUCTION SAFETY AND PHASING PLAN
OVERVIEW


DATE: 1/5/2023 SHEET: AC1 OF AC14















CLOSURE MARKER NOTES:


- 1. MAINTAIN RUNWAY CLOSURE MARKERS (P671.010.0000) AS CONSTRUCTION ALLOWS.
- 2. CLOSURE MARKER IS YELLOW, VINYL.
- RUNWAY CLOSURE MARKERS ARE TO BE PLACED AT EACH RUNWAY END AND AT
- 4. SECURE CLOSURE MARKERS WITH 50-LB YELLOW SANDBAGS ALONG THE EDGE OF THE CLOSURE MARKERS, SPACED NO GREATER THAN 5 FEET APART.



HAZARD MARKER BARRIER DETAIL


HAZARD MARKER BARRIER NOTES:

- 1. PLACE BARRIERS TO LIMIT ACCESS TO THE CLOSED APRON. USE LOW STYLE BARRIERS (LESS THAN 18 INCHES HIGH) WHEN ADJACENT TO AN ACTIVE MOVEMENT AREA.
- 2. HAZARD AREA BARRIERS ARE NOT TO BE PLACED WITHIN THE OFZ OF THE ACTIVE RUNWAY. CONSIDER PROP WASH WHEN PLACING BARRIERS.
- 3. SEE CSPP SECTION 16 FOR SPACING REQUIREMENTS.



TEMPORARY TRANSITION NOTES:


- 1. TEMPORARY TRANSITIONS SHALL BE SMOOTH AND FREE OF RUTS AND APPROVED BY THE ENGINEER PRIOR TO OPENING FOR AIRCRAFT
- 2. THICKNESS TO MATCH LAYER THICKNESS, OR AS NEEDED TO OBTAIN COMPACTION AS DIRECTED BY THE ENGINEER. USE CASC TO BUILD THE TEMPORARY TRANSITION. ALL ADDITIONAL WORK REQUIRED TO CONSTRUCT TEMPORARY TRANSITIONS IS SUBSIDIARY TO THE PROJECT. SUCH WORK MAY INCLUDE PLACEMENT, SCARIFYING, GRADING, COMPACTING, REMOVAL, REPLACEMENT, RE—COMPACTING, RE—GRADING, OR OTHER WORK AS REQUIRED TO ACCEPTABLY INCORPORATE MATERIALS INTO THE SUBSEQUENT WORK. NO SEPARATE MEASUREMENT OR PAYMENT WILL BE MADE.



6"x72" REFLECTIVE

TEMPORARY MARKER NOTES:


- 1. TEMPORARY RUNWAY EDGE MARKERS SHALL HAVE A WHITE RETRO REFLECTIVE SHEETING.
- 2. TEMPORARY THRESHOLD MARKERS SHALL HAVE A RED AND GREEN RETRO REFLECTIVE SHEETING. THE GREEN SIDE OF THE SHEETING SHALL FACE THE APPROACH OF THE RUNWAY, AND THE RED SIDE OF THE SHEETING SHALL FACE
- 3. TEMPORARY TAXIWAY EDGE MARKERS SHALL HAVE A BLUE RETRO REFLECTIVE SHEETING. SEE ELECTRICAL DEMOLITION PLANS FOR TEMPORARY TAXIWAY EDGE
- 4. TEMPORARY MARKERS PAID UNDER ITEM L-125.180.0000.
- 5. TEMPORARY LIGHTING FIXTURES TO BE EVENLY SPACED AT A MAXIMUM DISTANCE OF 200 FEET. SEE LIGHTING DEMOLITION AND TEMPORARY LIGHTING PLANS.




TEMPORARY RUNWAY MARKINGS DETAIL

TEMPORARY RUNWAY MARKING NOTES:

- TEMPORARY RUNWAY CENTERLINE MARKINGS ARE TYPICAL 120' STRIPES WITH 80' GAPS. SEE PLAN VIEW FOR NON-STANDARD STRIPE AND GAP DIMENSIONS.
- 2. TEMPORARY RUNWAY SURFACE MARKINGS PAID UNDER ITEM P620.070.0000.
- 3. TEMPORARY RUNWAY LIGHTING PAID UNDER ITEM L125.180.0000.





TEMPORARY RUNWAY THRESHOLD DETAIL

TEMPORARY RUNWAY MARKING NOTES:

- TEMPORARY RUNWAY THRESHOLD LIGHTS SHALL EMIT GREEN LIGHT OUTWARD FROM THE RUNWAY AND RED LIGHT
- 2. TEMPORARY RUNWAY THRESHOLD AND EDGE LIGHTS PAID UNDER ITEM L125.180.0000.
- 3. SEE ELECTRICAL FOR TEMPORARY RUNWAY THRESHOLD LIGHT DETAILS.

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-002-2023 CONSTRUCTION SAFETY AND PHASING PLAN

DETAILS

1/3/2023 AC7 of AC14


PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT OF AUTH NO AECC111


DATE


REVISION


BY


KWETHLUK AIRPORT
















TEMPORARY LIGHTING GENERAL NOTES:

- PROVIDE A TEMPORARY RUNWAY AND TAXIWAY LIGHTING SYSTEM AND TEMPORARY JUMPERS AS REQUIRED TO PROVIDE A FULLY OPERATIONAL LIGHTING SYSTEM TO THE SATISFACTION OF THE ENGINEER. REVISE AS NECESSARY TO COORDINATE WITH PROJECT PHASING AND MAINTAIN THE SYSTEM FOR THE DURATION OF THE PROJECT. TEMPORARY LIGHTING SYSTEM SHALL MEET THE REQUIREMENTS OF A MEDIUM INTENSITY LIGHTING SYSTEM PER AC 150/5340-30J. PAID FOR UNDER L125.180.0000.
- 2. TEMPORARY LIGHTING SYSTEM WILL REQUIRE A 5KV REGULATOR BASED ON CALCULATIONS USING INCANDESCENT LAMPS AND L861SE THRESHOLD
- 3. RESTORE AIRFIELD LIGHTING POWER AND CONTROL CIRCUITS ONE HOUR PRIOR TO ANY SCHEDULED FLIGHT, OR AS DIRECTED BY THE PROJECT ENGINEER.
- 4. WHEN TEMPORARY LIGHTING IS NO LONGER NEEDED, REMOVE UNUSED COMPONENTS, CONDUIT AND WIRING.
- 5. TEMPORARY JUMPERS SHALL BE #8 AWG, 5KV, TYPE 'C' AIRPORT CABLE. RUN JUMPERS IN HDPE CONDUIT, 1-1/4IN MINIMUM, AND 50 LBS SAND BAG EVERY 10 FT ON CENTER. ELECTRICAL CONNECTORS SHALL BE FIELD ATTACHED PLUG-IN SPLICES PER SECTION L-108. TEMPORARY JUMPERS SHALL BE SUBSIDIARY TO ITEM L125.180.0000 AND NO SEPARATE PAYMENT WILL BE MADE.
- 6. TEMPORARY LIGHT BASES SHALL BE CONSTRUCTED OF STEEL CHANNEL. BOLT THE FIXTURE BASE PLATE TO THE CHANNEL AND SECURE IN PLACE WITH SAND BAGS. AT THE CONTRACTOR'S OPTION, AND THE ENGINEER'S APPROVAL, A SELF-CONTAINED TEMPORARY LIGHTING SYSTEM MAY BE PROVIDED. SECURE THE LIGHTS IN PLACE PER THE MANUFACTURER'S INSTRUCTIONS.
- 7. PROVIDE 1/2IN BLANK STEEL COVERS PER SAFETY PLAN OR AS DIRECTED BY THE ENGINEER AND SECURE TO LIGHT BASES.
- REMOVE EDGE LIGHTS THAT CONFLICT WITH CONSTRUCTION ACTIVITIES AND PROVIDE MEANS OF BLANKING OUT EXISTING TAXIWAY EDGE LIGHTS AND SIGNS ON CLOSED PORTIONS OF TAXIWAYS AND APRON AS INDICATED IN THE PHASING PLANS AND AS DIRECTED BY THE ENGINEER. THIS MAY BE ACCOMPLISHED BY REMOVING THE FIXTURES AND PROVIDING SHORTING CAPS, OR BY BAGGING THE FIXTURES AND SIGNS. IF FIXTURES ARE REMOVED, PROVIDE STEEL COVER PLATES. THE CONTRACTOR SHALL PROVIDE SAFE STORAGE AND RE-INSTALL THE FIXTURES OR REMOVE BAGS, AND CLEAN EACH FIXTURE AT THE END OF EACH PHASE. THIS WORK SHALL BE PAID UNDER ITEM L125.180.0000 AND NO SEPARATE PAYMENT WILL BE MADE.





\TEMPORARY RUNWAY EDGE LIGHT DETAIL

MBA CONSULTING ENGINEERS, INC. 3812 SPENARD ROAD, SUITE 200 (907) 274-2622

NO. AECC578

CERTIFICATE OF AUTHORIZATION BY DATE REVISION


STATE OF ALASKA DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES **CENTRAL REGION**

PHONE (907) 269-0590

1/4/2023 AC140FAC14

1 TEMPORARY THRESHOLD LIGHT BAR

KWETHLUK AIRPORT KWETHLUK, ALASKA AIRPORT REHABILITATION PROJECT No. CFAPT00682 AIP No. 3-02-0435-XXX-20XX TEMPORARY LIGHTING NOTES, DETAILS 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 AND LEGEND



PS&E REVIEW

KWETHLUK AIRPORT

KWETHLUK, ALASKA SNOW REMOVAL EQUIPMENT BUILDINGS PROJECT No. CFAPT00801 AIRPORT IMPROVEMENT PROGRAM A.I.P. No. 3-02-0435-XXX-2023

SHEET TITLE	SHEET No.	· · · · · · · · · · · · · · · · · · ·
GENERAL TITLE SHEET	G1 OF G1	<u>ELECTRICAL</u> ELECTRICAL LEGENDS
CIVIL EXISTING SITE & DEMOLITION PLAN SITE PLAN GRADING PLAN TYPICAL SECTIONS & DETAILS ARCHITECTURAL ARCHITECTURAL FLOOR PLAN ARCHITECTURAL ROOF PLAN ARCHITECTURAL EXTERIOR ELEVATIONS	C1 OF C4 C2 OF C4 C3 OF C4 C4 OF C4 A1 OF A6 A2 OF A6 A3 OF A6	SITE PLAN SREB No.1 LIGHTING PLAN SREB No.1 POWER PLAN CONTROL DETAILS POWER DETAILS LIGHTING SCHEDULE AND AIC PANEL SCHEDULES SREB No.2 LIGHTING PLAN SREB No.2 POWER PLAN
ARCHITECTURAL BUILDING SECTIONS ARCHITECTURAL DETAILS ARCHITECTURAL DETAILS	A4 OF A6 A5 OF A6 A6 OF A6	
STRUCTURAL STRUCTURAL NOTES & CRANE PLAN FRAMING PLANS DECK PLANS SKID SECTION STRUCTURAL DETAILS STRUCTURAL DETAILS STRUCTURAL DETAILS STRUCTURAL DETAILS STRUCTURAL DETAILS STRUCTURAL DETAILS FOUNDATION & MISC DETAILS	S1 OF S9 S2 OF S9 S3 OF S9 S4 OF S9 S5 OF S9 S6 OF S9 S7 OF S9 S8 OF S9 S9 OF S9	
MECHANICAL LEGEND, SCHEDULES, AND DETAILS MECHANICAL FLOOR PLAN SREB No. 1 MECHANICAL DETAILS COMPRESSED AIR SCHEMATIC AND DETAILS MECHANICAL FLOOR PLAN SREB No. 2	M1 OF M5 M2 OF M5 M3 OF M5 M4 OF M5 M5 OF M5	

SPONSORED BY
STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION

APPROVED	DATE
IELANIE ARNOLDS, P.E.	DIVISION OF FACILITIES SERVICES DIRECTOR

APPROVED DATE

MATTHEW EPP, P.E. PROJECT MANAGER

KWETHLUK AIRPORT SNOW REMOVAL EQUIPMENT BUILDINGS

SHEET No.

E1 OF E10

E2 OF E10 E3 OF E10

E4 OF E10

E5 OF E10

E6 OF E10

E7 OF E10


E8 OF E10


E9 OF E10 E10 OF E10


PROJECT No. CFAPT00801


SHEET G1 OF G1


Trouted 0/20/2022 2.04 FW by coley riewert Z:\project\2986.01 DOT_SWPF Kwethluk SREB\Civi\ACAD\2986.01-G1 1


























LIVE LOAD	FLOOR ROOF	200 PSF 20 PSF
SNOW LOAD	GROUND SNOW LOAD, Pg Importance factor, ie Exposure factor, ce	40 PSF 1.00 0.9
	THERMAL FACTOR, Ct	1.0
	FLAT ROOF SNOW LOAD, PF SNOW DRIFT	32 PSF PER ASCE 7-16

WIND LOAD	WIND SPEED (3-SECOND GUST)	119 MPH
	ENCLOSURE CLASSIFICATION	ENCLOSED
	EXPOSURE CATEGORY	С
	IMPORTANCE FACTOR, IW	1.00
	TOPOGRAPHIC FACTOR, Kzt	1.00
	DIRECTION FACTOR, Kd	0.85
	GUST FACTOR, G	0.88
	INTERNAL PRESSURE COEF. GCpi	+/- 0.18

SEISMIC	SS= 0.300g, S1=0.125g, SDS = 0	312g, SD1 = 0.195g			
	SEISMIC DESIGN CATEGORY	С			
	SITE CLASS	D			
	IMPORTANCE FACTOR, Is	1.00			
	RESPONSE MOD FACTOR, R				
	MOMENT FRAME	3.5			
	BRACED FRAME	3.25			
	OVERSTRENGTH, OMEGA				
	MOMENT FRAME	3.0			
	BRACED FRAME	2.0			
SPECIAL LOADS:	MINIMUM COLLATERAL LOAD	5 PSF			

MATERIALS

COMPLY WITH BUY AMERICAN PREFERENCE REQUIREMENTS OF FAA FUNDED PROJECT.

MONORAIL HOIST CAPACITY

STRUCTURAL STEEL SHALL CONFORM TO IBC CHAPTER 22, FOR ASTM SPECIFICATION A-36, Fy = 36 ksi EXCEPT WHERE NOTED OTHERWISE. ROLLED SHAPES SHALL BE ASTM A992, 50 ksi YIELD.

4.000 LBS

- STEEL TUBING (HSS) SHALL CONFORM TO ASTM A500, GRADE B, Fy = 46 ksi.
- DESIGN FABRICATION AND ERECTION SHALL BE IN ACCORDANCE WITH THE IBC CHAPTER 22, DIVISION IX, ALLOWABLE STRESS DESIGN.
- ALL BOLTS (UON) SHALL BE A325 HIGH STRENGTH BOLTS IN CONFORMANCE WITH AISC STANDARD "SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS".
- MACHINE BOLTS SHALL CONFORM TO ASTM 307, UNLESS NOTED OTHERWISE AND SHALL BE PROVIDED HEAVY HEX HEAD NUTS CONFORMING TO ASTM A563, GRADE A AND CIRCULAR STEEL WASHERS CONFORMING TO ASTM F436.
- WELDING PER AWS 1.1 WITH E70 ELECTRODES.
- METAL GRATE: 2"x5/16" BRG BARS @ 1 3/8" C/C, w/ WELDED CROSS BARS 3/4"x3/16" @ 4" C/C, ENDS BANDED w/ 1/8" FLAT BAR, HOT DIP GALVANIZED, FABRICATE IN 3' MAX
- PROVIDE ADEQUATE LATERAL BRACING FOR STRUCTURE DURING FABRICATION. PLAN WELDING SEQUENCE TO ELIMINATE WARPAGE OF SKID.

REFERENCE P-610FOR CONCRETE REQUIREMENTS. 3,000 PSI MINIMUM SACK CRETE OR BETTER. SUBMIT FOR REVIEW AND APPROVAL.

AT UNDERSIDE OF FLOOR PLATE & ON JOIST FRAMING: SPRAY APPLY "URETHANE" FOAM INSULATION IN ACCORDANCE WITH SPEC 072129.

1. PAINT ALL COMPONENTS PER SPEC SECTION 051210. FLOOR COLOR SHALL BE GRAY.

PRIOR TO ACCEPTANCE OF THE SREB SKIDS FOR SHIPPING FROM THE POINT OF FABRICATION, THE PERIMETER MEMBERS OF THE SKID FRAMEWORK FOR STRAIGHTNESS. WARPAGE OF THE SKID FRAME EXCEEDING 1/2" (ASSUMING THE BASE LINE IS A STRAIGHT LINE BETWEEN THE ENDS OF THE SKID DECK) SHALL BE CAUSE FOR REJECTION OR SHALL REQUIRE REPAIRS BY THE FABRICATOR TO MEET SUCH TOLERANCE. PROVIDE COPY OF MEASUREMENTS WITH CERTIFICATION LETTER BY QC MANAGER.

2. PRIOR TO ACCEPTANCE OF THE SREB SKIDS FOR ASSEMBLY OF THE BUILDING STRUCTURAL FRAMEWORK, THE PERIMETER MEMBERS OF THE SKID FRAMEWORK SHALL BE CHECKED FOR STRAIGHTNESS BY THE ENGINEER. WARPAGE OF THE SKID FRAME EXCEEDING 1/2" (ASSUMING THE BASE LINE IS A STRAIGHT LINE BETWEEN THE ENDS OF THE SKID DECK) SHALL BE CAUSE FOR REJECTION OR SHALL REQUIRE REPAIRS BY THE FABRICATOR TO MEET SUCH

SPECIAL INSPECTION

- THE FOLLOWING SPECIAL INSPECTIONS SHALL BE PERFORMED BY QUALIFIED PERSONNEL EMPLOYED BY THE STATE OR ITS AGENT. THE CONTRACTOR SHALL COORDINATE WORK WITH THE SPECIAL INSPECTORS.
- 2. SPECIAL INSPECTORS SHALL OBSERVE THE WORK ASSIGNED FOR CONFORMANCE WITH APPROVED DESIGN DRAWINGS AND SPECIFICATIONS. INSPECTION REPORTS SHALL BE FURNISHED TO THE OWNER AND THE ENGINEER OF RECORD. ALL DISCREPANCIES SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE CONTRACTOR FOR CORRECTION, AND TO THE ATTENTION OF THE ENGINEER OF RECORD.
- 3. THE SPECIAL INSPECTORS SHALL SUBMIT A FINAL SIGNED REPORT STATING WHETHER THE WORK REQUIRING SPECIAL INSPECTION WAS, TO THE BEST OF THE INSPECTOR'S KNOWLEDGE, IN CONFORMANCE WITH THE APPROVED PLANS AND SPECIFICATIONS AND THE APPLICABLE WORKMANSHIP PROVISION OF THE APPLICABLE CODES.
- 4. PROVIDE THE FOLLOWING SPECIAL INSPECTIONS PER SECTION 1704 OF THE INTERNATIONAL BUILDING CODE. ITEMS MARKED BY AN ASTERIC (*) MAY BE INSPECTED BY THE RESIDENT PROJECT ENGINEER IF SPECIAL INSPECTOR IS NOT AVAILABLE.

BUILDING FRAME:

- 1. ANCHOR BOLTS: VERIFY SNUG TIGHT OR AS OTHERWISE SPECIFIED BY THE BUILDING DESIGNER (PERIODIC)*
- 2. HIGH STRENGTH BOLTS: VERIFY MARKINGS INDICATING TYPE OF BOLT MEETS THOSE REQUIRED BY CONSTRUCTION DOCUMENTS. FOR BOLTS TIGHTENED BY TURN-OF-THE-NUT METHOD, VERIFY CONNECTION PLYS HAVE BEEN DRAWN TOGETHER AND PROPERLY SNUGGED AND MONITOR INSTALLATION OF BOLTS TO VERIFY PROPER PROCEDURES (CONTINUOUS). FOR LOAD INDICATING WASHERS OR TWIST-OFF BOLTS, VERIFY UPON COMPLETION (PERIODIC).
- 3. INSPECT STEEL FRAME JOINT DETAILS INCLUDING MOMENT FRAME CONNS, FRAME BRACING AND FLANGE BRACING OF PRIMARY BUILDING FRAMES (PERIODIC)*
- BUILDING IS PRE-ENGINEERED METAL BUILDING, PROVIDE ANY SPECIAL INSPECTIONS REQUIRED BY THE BUILDING DESIGNER.

- VISUAL INSPECTION OF WELDS
- VERIFY WELDER QUALIFICATIONS
- REVIEW WELDING PROCEDURES 4. VERIFY MATERIALS CERTIFICATIONS

STRUCTURAL ABBREVIATIONS: AMERICAN INSTITUTE OF

STEEL CONSTR

ASTM AMERICAN SOCIETY FOR TESTING & MATERIALS BLKG BLOCKING BTWN BETWEEN BOT BRG BEARING C/C CL CLR CENTER TO CENTER CENTERL INE CLEAR COL CONC COLUMN CONCRETE CONF I G CONFIGURATION ksi CONNECTION CONT CONTR CONTRACTOR CONSTR DEPTH, DEEP DEFL DET DIA, DEFLECTION, DEFLECTOR Ø DIAMETER DIAGONAL EACH END

FEDERAL AVIATION ADMINISTRATION FOUNDATION FLG FLR FLANGE FI OOR FAR SIDE, FULL SIZE GALVANIZED HEAVY DUTY HOT DIP GALVANIZE HEADER HORIZONTAL HOLLOW STRUCTURAL SECTION INSIDE DIAMETER THAT IS, IN OTHER WORDS INTERIOR KILOPOUND PER SQUARE INCH ANGLE LBS LG LONG POUNDS LONGITUDINAL MI MAX MALEABLE IRON MAXIMUM MID MIN OC OPG OD OF MIDDLE MINIMUM ON CENTER OPENING OUTSIDE DIAMETER OUTSIDE FACE

PRE ENGINEERED METAL

POUNDS PER SQUARE FOOT

PENETRATION

PLYWOOD

PEMB

PFN

POLYVINYL CHLORIDE QUARTER RAII ING SHEET SIMIL AR SQUARE SREB SNOW REMOVAL EQUIPMENT

STEEL STIFFENER SUPPORT SEA WATER LEVEL SYMMETRICA TOP & BOTTOM TRANSITION TRANS TUBE STEEL TYPICAL

UNIFIED COARSE THREAD UNLESS OTHERWISE NOTED VERTICAL


WIDE "W" STYLE BEAM WIDE FLANGE BEAM "WT" STYLE BEAM

OVERHEAD HOIST MONORAIL CENTERLINE CENTERLINE OF DOOR = CENTERLINE OF MONORAIL '5' MAX'

- 1. CONTRACTOR SHALL COORDINATE AND VERIFY THE HOOK CLEARANCE WITH DOT&PF EQUIPMENT. BOTTOM OF HOOK HEIGHT SHALL BE A MINIMUM OF 13' ABOVE FINISH FLOOR, BUT MUST BE VERIFIED AND COORDINATED BY CONTRACTOR BEFORE
- SOUTH SREB SHOWN. MIRROR ABOUT BUILDING CENTERLINE FOR NORTH SREB CONTRACTOR SHALL INSTALL MONORAIL IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS. TROLLEY AND CHAIN HOIST ARE NOT TO BE INSTALLED, BUT
 - SHALL BE DELIVERED TO THE DOT&PF EQUIPMENT FOREMAN IN BETHEL, AK: BETHEL DOT EQUIPMENT FOREMAN

3500 STATE HWY BETHEL, AK 99559 (907) 543-3760

OVERHEAD CRANE (MONORAIL) NOT TO SCALE



TYPICAL SREB SECTION

NOT TO SCALE

- OWNER EQUIPMENT SHOWN FOR
- 2. EVAPORATION TRENCHES NOT SHOWN

Joshua Crowe CE - 13332

FOR FXAMPLE

EACH WAY

ECONOMY ELEVATION

EACH SIDE

EXPANSION

EXTERIOR

ECON ELEV, EL

EX, EXC

PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT. OF AUTH. NO. AECC111 BY DATE **REVISION**

UON

VERT

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502

PHONE (907) 269-0590


PS&E REVIEW KWETHLUK AIRPORT


KWETHLUK, ALASKA SNOW REMOVAL EQUIPMENT BUILDINGS PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023 STRUCTURAL NOTES AND


CRANE PLAN


S1 of S9

09/09/2022












TYP BRACING DETAIL @ EXTERIOR SCALE: 1 1/2"=1'-0"



TYP JOINT CONNECTION SCALE: 1 1/2"=1'-0"



TYP BRACING DETAIL @ INTERIOR SCALE: 1 1/2"=1'-0"




1. CHANCE HELICAL WITH 2 7/8"ø SHAFT, 10" HELIX WITH 8' BURY MAY MAY BE USED IN LIEU OF TURNBUCKLE/ SHACKLE DETAIL

- 2. BELOW GRADE STEEL SHALL BE HOT DIP GALV AFTER FABRICATION
- 3. DECK PLATE AND COLUMN BEARING PLATE NOT SHOWN FOR

TYP HOLD DOWN DETAIL


SCALE: 1 1/2"=1'-0"

Joshua Crowe CE - 13332




L5X3 JOIST HEADER, TRIM VERT LEG TO MATCH FLOOR SLOPE -3/8" STEEL DECK $\rho_{3/16}$ C4 JOIST (2) 1"ø F3125 -GRADE A325 THRU BOLTS @ SKID QTR PTS 3 SIDES /WELD NUT TO 'C', TYP AND HALFWAY BETWEEN EA GRIDLINE. CONTINUOUS BEARING PLATE





TYP DECK PLATE JOINT SECTION SCALE: 1 1/2"=1'-0"




TYP BLOCKING SECTION SCALE: 1 1/2"=1'-0"


PS&E REVIEW


KWETHLUK AIRPORT
KWETHLUK, ALASKA
SNOW REMOVAL EQUIPMENT BUILDINGS STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** 09/09/2022 **AND PUBLIC FACILITIES** PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023 **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590 STRUCTURAL DETAILS

S5 of S9




EVAP. TRENCH LONGITUDINAL SECTION





EVAP. TRENCH DETAIL @ END







NOTES:

- 1. WHERE TOP OF L2x2 IS WITHIN 1/4" OF TOP OF JOIST, SUBSTITUTE 1" PJP GROOVE WELD FOR FILLET WELD.
- 2. WELD INSIDE 1" DIA. HOLES IN PLATE @ 16" O.C.


FLOOR JOIST BEYOND END OF TRENCH T FLOOR SCALE: 3"=1'-0"





NOTES:
1. COMPLETE THIS WELD PRIOR TO PLACING C4





- NOTES:

 1. TRENCH PAN ASSEMBLY INCLUSIVE OF PERIMETER HSS FRAME SHALL BE SHIPPED LOOSE.
- HOT-DIPPED GALVANIZED AND SHIPPED LOOSE.

 2. TRENCH PAN ASSEMBLY SHALL BE WELDED AS FOR HYDROCARBON CONTAINMENT AND BE LEAK-TESTED PRIOR TO HOT-DIPPED GALVANIZE
- 3. FIELD-INSTALL TRENCH PAN ASSEMBLY INTO OPENING AFTER ASSEMBLY OF



OF AL TO		
49 ⊞ 🔭 ★ 🔭	PLANS DEVELOPED BY:	T
	R&M CONSULTANTS, INC.	L
Joshua Crowe	9101 VANGUARD DR.	
CE 13332	ANCHORAGE, AK 99507	
	(907) 522-1707	ı


PLANS DEVELOPED BY:				
R&M CONSULTANTS, INC.				DEI
9101 VANGUARD DR.				
ANCHORAGE, AK 99507				
(907) 522-1707				411
CERT. OF AUTH. NO. AECC111	BY	DATE	REVISION	7


STATE OF ALASKA PARTMENT OF TRANSPORTATION **AND PUBLIC FACILITIES CENTRAL REGION** 111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA SNOW REMOVAL EQUIPMENT BUILDINGS PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023 STRUCTURAL DETAILS


09/09/2022 S6 of S9


PS&E REVIEW






SCALE: 1 1/2"=1'-0







TYP TOW BAR SECTION @ EXTERIOR SCALE: 1 1/2"=1'-0"

Joshua Crowe CE - 13332

PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT OF AUTH NO AECC11 BY DATE **REVISION**

NOTE: HSS BRACE NOT SHOWN

FOR CLARITY.

STATE OF ALASKA **AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

PAD EYE

PS&E REVIEW KWETHLUK AIRPORT
KWETHLUK, ALASKA
SNOW REMOVAL EQUIPMENT BUILDINGS 09/09/2022

PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023 STRUCTURAL DETAILS

(OPP)

STEEL COLUMN PER

-ANCHOR BOLTS PER BLDG MFGR

STIFF PLATE -BOTT FLANGE, W18

TYP COLUMN BEARING SECTION


SCALE: 1 1/2"=1'-0'


BUILDING MANUFACTURER

3 SIDES TYP


S7 **of** S9

DEPARTMENT OF TRANSPORTATION






N TYP TOW BAR SECTION @ INTERIOR S2 SCALE: 1 1/2"=1'-0"




TOW BAR SPLICE
Scale: 1 1/2"=1'-0"



TYP HSS CONNECTION DETAIL

SCALE: 1 1/2"=1"-0"



P TYP W12 LUMBER SUPPORT
S2 SCALE: 1 1/2"=1'-0"


FLOOR PLATE AND
FRAMING NOT SHOWN

(2) 5/8 H.D. GALV
BOLTS w/ MI WASHERS

6x8 PT (FOR
GROUND CONTACT)
SILL @ PERSONNEL
DOOR. WIDTH FROM
INSIDE TO INSIDE
EDGE OF WALL
PANEL @ DOOR
JAMBS.




PS&E REVIEW




Joshua Crowe CE - 13332 STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION
4111 AVIATION AVE., ANCHORAGE ALASKA 99502
PHONE (907) 269-0590

KWETHLUK AIRPORT
KWETHLUK, ALASKA
SNOW REMOVAL EQUIPMENT BUILDINGS
PROJECT NO. CFAPTOOBO1
AIP NO. 3-02-0435-XXX-2023
STRUCTURAL DETAILS

09/09/2022 SHEET: \$8 OF \$9







Joshua Crowe CE - 13332

FOLDING DOOR BRACE

SCALE: 3"=1'-0"



EXTERIOR BOLLARD DETAIL C2 /



-EXT FIXTURE (LIGHTS, GUARDS. ETC.) 3/4" PLWD— BACKING. SIZE 3 TIMES LARGER THAN FIXTURE BASE MINIMUM WALL GIRTS SEAL WITH 100% SILICONE -FUEL BRACKET 5/8" H.D. GALV BOLT CHANNEL--3/4"øx 2-1/2" OR Z-GIRT GALV PIPE w/ CLIPS TO SLEEVE WALL GIRTS 2-1/2" WALL PANEL

ICE DEFLECTOR @ EXT LIGHTS & FUEL LINE

TYP WALL MOUNT DETAIL

PS&E REVIEW

PLANS DEVELOPED BY: R&M CONSULTANTS, INC. 9101 VANGUARD DR. ANCHORAGE, AK 99507 (907) 522-1707 CERT. OF AUTH. NO. AECC111 BY DATE **REVISION**

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA SNOW REMOVAL EQUIPMENT BUILDINGS PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023 FOUNDATION & MISC DETAILS

09/09/2022 S9 **of** S9

	LEGEND & ABBREVIATIONS	S
ABBR.	EXPLANATION	SYMBOL
Α	AIR - COMPRESSED	— A —
	AIR FOIL TURNING VANES	⊢ A
AAV	AUTOMATIC AIR VENT	
AFF	ABOVE FINISHED FLOOR	+ +
BDD	BACKDRAFT DAMPER	
BD	BALANCING DAMPER	1 + 1
- คบ		
	BALANCING/ISOLATION VALVE	<u></u> —
	BALL VALVE	<u></u> ——₩—
CFM	CUBIC FEET/MINUTE	
CO	CLEANOUT	
CV	CHECK VALVE	<u> </u>
DN	DOWN	
(E)	EXISTING	
E/A	EXHAUST AIR	
	EXPANSION COMPENSATOR	——I
FCO	FLOOR CLEANOUT	- ⊗
FD	FLOOR DRAIN	T a
	FLEXIBLE CONNECTION	t - i-
	FLEXIBLE DUCT	
F00	FLOW CONTROL VALVE	
FOS	FUEL OIL SUPPLY	—FOS—
FOR	FUEL OIL RETURN	—FOR—
	GLOBE VALVE	——₩——
GPM	GALLONS PER MINUTE	į į
ID	INSIDE DIAMETER	
MOD	MOTOR OPERATED DAMPER	
MOV	2-WAY MOTOR OPERATED VALVE	
MOV	3-WAY MOTOR OPERATED VALVE	
	NATURAL GAS	— G —
N.C.	NORMALLY CLOSED	
0/A	OUTSIDE AIR	
OD		
OD	OUTSIDE DIAMETER	2.5
	PIPE ANCHOR	- ×
/	PIPE GUIDE	<u> — × — </u>
POC/POD	POINT OF CONNECTION/DISCONNECT	<u> </u>
	PRESSURE GAGE	₩0
PRV	PRESSURE RELIEF VALVE	——————————————————————————————————————
R/A	RETURN AIR	
RV	RELIEF VALVE	*
	RETURN AIR SLOT	
	RETURN/EXHAUST AIR REG. OR GRILLE	Ø.
	, , , , , , , , , , , , , , , , , , , ,	
S	SANITARY SOIL	
S S/A	SANITARY SOIL SUPPLY AIR	<u> </u>
S S/A	SUPPLY AIR	
	SUPPLY AIR SQUARE HEAD COCK	
S/A	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE	
S/A SD	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN	
S/A SD SL	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT	
S/A SD	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL	
S/A SD SL	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR	
S/A SD SL	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL	
S/A SD SL	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR	
S/A SD SL SS	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR THERMALLY INSULATED DUCT OR PIPE	-SDSSSSSE
S/A SD SL	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR THERMALLY INSULATED DUCT OR PIPE THERMOMETER THERMOSTAT	-SDSSSS
S/A SD SL SS	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR THERMALLY INSULATED DUCT OR PIPE THERMOMETER THERMOSTAT UNION	SD
S/A SD SL SS T'STAT	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR THERMALLY INSULATED DUCT OR PIPE THERMOMETER THERMOSTAT UNION VENT THRU ROOF	
S/A SD SL SS T'STAT VTR WCO	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR THERMALLY INSULATED DUCT OR PIPE THERMOMETER THERMOSTAT UNION VENT THRU ROOF WALL CLEANOUT	SD - SS -
S/A SD SL SS T'STAT	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR THERMALLY INSULATED DUCT OR PIPE THERMOMETER THERMOSTAT UNION VENT THRU ROOF WALL CLEANOUT	SD S
S/A SD SL SS T'STAT VTR WCO	SUPPLY AIR SQUARE HEAD COCK STRAINER WITH DRAIN VALVE STORM DRAIN ACOUSTICALLY LINED DUCT STAINLESS STEEL STATIC PRESSURE SENSOR THERMALLY INSULATED DUCT OR PIPE THERMOMETER THERMOSTAT UNION VENT THRU ROOF WALL CLEANOUT	SD - SS -

THIS IS A STANDARD LEGEND, SOME SYMBOLS SHOWN ON LEGEND ARE NOT NECESSARILY ON THE DRAWING.

CODE SUMMARY

VENTILATION PROVIDED IN ACCORDANCE WITH IMC 402, NATURAL VENTILATION. REQUIRED OPENING AREA (4% PER IMC 402.2), 52 SF ACTUAL OPENING AREA, 280 SF (FOLDING DOOR)

MOTOR VEHICLE OPERATION PER IMC 502.14: MOTOR VEHICLES ARE ASSUMED TO OPERATE INSIDE ONLY FOR THE DURATION NECESSARY TO MOVE THE MOTOR VEHICLE IN AND OUT OF THE BUILDING. PER EXCEPTION 3, THIS SECTION DOES NOT APPLY.

MECHANICAL VENTILATION WITH CO2/NOX DETECTION IS PROVIDED BY OWNER REQUEST.

	FAN SCHEDULE													
SYMBOL	LOCATION	CFM	S. TOT	P. EXT	RPM	O.V. FPM		PE WHL	USE	MOTOR HP/VOLTS/PH	DESIGN BASIS PRODUCT			
EF-1	STORAGE 101	975	-	0.4	1345	1	PROP			1/2 /115/1	GREENHECK MODEL SE1-14-440-VG, EC MOTOR, DIAL ON MOTOR FOR BALANCING.			
											OSHA GUARD. TIMER: INTERMATIC FF30MC.			
F-1	STORAGE 101	12,500	1	1	400	ı	PADL	36	DE- STRAT	0.35A/120/1	VES ENVIRONMENTAL MODEL IND-A364-L WITH ICFC2.5 SPEED CONTROL. TIMER: INTERMATIC			
											FF312H			

HEATING UNIT SCHEDULE													
YMBOL	TYPE	FLUID		/DRO	NIC MBH	GPM	ELEC. KW	OIL IN	MBH OUT	CFM	RPM	MOTOR HP/VOLTS/PH	DESIGN BASIS PRODUCT
JH-1,	UNIT HEATER							231	185			1/3/115/1	MODINE POR185, #1 DIESEL/FUEL OIL, 1.65 GPH. TIMER: INTERMATIC FF312H,
2													THERMOSTAT: HONEYWELL T631C1012


					TANK	SCHEDULE
SYMBOL	FUNCTION	MEDIUM	TOTAL VOLUME GALLONS	MATERIALS	LABEL	DESIGN BASIS PRODUCT
(E)FT-1	HEATING FUEL	FUEL OIL	1000	STEEL		EXISTING 1000 GALLON HEATING TANK
(E)FT-2	FUEL DISPENSING	DIESEL		STEEL		EXISTING DISPENSING TANK
FT-3	HEATING FUEL	FUEL OIL	1000	STEEL	UL2085	ANCHORAGE TANK FIREGUARD AT1MFGR RECTANGULAR, 88Lx72Wx50H
DT-1	DAY TANK	FUEL OIL	10	STEEL		SIMPLEX STS SERIES W/ PCB 1 CONTROLS, WALL MOUNT, GRAVITY FEED TO UNIT HEATERS, 063 VENT CAP. DUPLEX REMOTE FUEL
						PUMPS: 1/3 HP MOTOR, 115V/60HZ/1PH.


MECHANICAL EQUIPMENT LIST


AIR COMPRESSOR: INGERSOLL RAND 2475N5P, 80 GALLON MINIMUM. 16.8 ACFM @ 175 PSI, 5 HP, 1.15 S REGULATOR, AUTOMATIC CONDENSATE DRAIN W/ HIGH MOUNT ELECTRIC CONDENSATE DRAIN EDV-2000 (115V, 3-PRONG CORD). HOSE REEL WHERE SHOWN: AUTO RETRACTABLE SPEEDAIRE MODEL NO. 2CUA7 LOW PRESSURE, 50 FOOT, 3/8"


NOTE: FURNISH AND INSTALL MAKES AND MODELS CITED HERE OR IN THE SPECIFICATIONS OR APPROVED EQUALS


			F	LE							
SYMBOL	SERVICE	FLUID	GPM HEAD FT.	RPM	MOTOR HP/VOLTS/PH	DESIGN BASIS	PRODUCT				
PMP-1	FUEL	DIESEL	20.0 -	-	1/3 /115/1	FILL-RITE FR710VN NO77LE AND METER	W/ ARCTIC	COLD	WEATHER	HOSE,	REEL,





















PS&E REVIEW


KWETHLUK AIRPORT STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590


KWETHLUK, ALASKA SNOW REMOVAL EQUIPMENT BUILDINGS PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023 LEGEND, SCHEDULES, AND DETAILS


09/09/2022

M1 of M5









SITE LEGEND					
OVERHEAD ELECTRICAL					
UNDERGROUND ELECTRICAL					
FENCE					
UTILITY POLE					

LINE TYPE LEGEND
 EXISTING
 NEW
 DEMOLITION


	LIGHTING LEGEND
~	
⊢ Q	WALL MOUNT
\oslash	SURFACE MOUNT
0	RECESSED
	2X2 LIGHTING FIXTURE RECESSED
	2X4 LIGHTING FIXTURE RECESSED
	2X2 SURFACE MOUNT
	2X4 SURFACE MOUNT
\vdash	WALL MOUNT
lacktriangle	EXTERIOR LIGHT SINGLE WITH POLE MOUNT
$\vdash\!\!\!\!-\!$	PHOTOCELL
©	OCCUPANCY SENSOR CEILING MOUNT
\$к	KEY OPERATED SWITCH
\$ LM	SWITCH, LOW VOLTAGE MASTER
\$p	SWITCH WITH PILOT LIGHT
\$0	OCCUPANCY SENSOR SWITCH
\$	SWITCH, SINGLE POLE
\$2	SWITCH, DOUBLE POLE
\$3	SWITCH, THREE-WAY
\$4	SWITCH, FOUR-WAY
MD	MOTION DETECTOR
\Box	EMERGENCY LIGHT BATTERY POWERED
42	EMERGENCY LIGHT REMOTE HEAD
$\vdash \otimes$	EXIT SIGN WALL MOUNTED SHADOWING INDICATES FACE
•	EXIT SIGN CEILING MOUNTED SHADOWING INDICATES FACE
1\$1	EXIT SIGN DOUBLE FACE ARROWS INDICATE CHEVRONS
•	EMERGENCY LIGHTS
	INVERTER

	POWER LEGEND
_	ELECTRICAL POWER PANEL
	ELECTRICAL DISTRIBUTION PANEL
	ELECTRICAL LIGHTING PANEL
	PANELBOARD CABINET FLUSH MOUNT
<i>IIIIIII</i>	PANELBOARD CABINET SURFACE MOUNT
X WIDE / X DEEP	SWITCHBOARD NEW
X WIDE / X DEEP	SWITCHBOARD EXISTING
\bigcirc	METER
\boxtimes	CONTROLLER/DISCONNECT
	UNFUSED DISCONNECT
	FUSED DISCONNECT
	VARIABLE FREQUENCY DRIVE
\boxtimes	CONTROLLER
HH	CONTACTOR
9	MOTOR SINGLE PHASE
(x)	MOTOR SINGLE PHASE : X = HORSE POWER
\$ \$ \$ \$	MOTOR 3PH
(MOTOR 3PH : X = HORSE POWER
©	GENERATOR POWER
T	TRANSFORMER
\$т	THERMAL SWITCH

	GROUNDING LEGEND	
	TEE CONNECTION	
	CROSS CONNECTION	
•	GROUND ROD	
	GROUND ROD CONNECTION-2	
	GROUND ROD CONNECTION-1	
	BURIED CABLE	
•	BONDING POINT	
<u>=</u>	EARTH GROUND	
\forall	GROUND ROD	
	LIGHTNING ARRESTOR	

WIRING DEVICES LEGEND					
PUSH BUTTON					
JUNCTION BOX					
RECEPTACLE - DUPLEX CEILING MOUNT					
RECEPTACLE - DUPLEX FLOOR MOUNT					
RECEPTACLE - DUPLEX ON EMERGENCY POWER					
RECEPTACLE - DUPLEX ISOLATION GROUND					
⊕ RECEPTACLE - QUAD					
→ RECEPTACLE - SINGLE					
RECEPTACLE - X-NEMA CALLOUT					
OR CONPECTION					
RECEPTACLE - GENERATOR PLUG IN					

DRAWING SCHEDULE					
E1	ELECTRICAL LEGENDS				
E2	SITE PLAN				
E3	SREB No.1 LIGHTING PLAN				
E4	SREB No.1 POWER PLAN				
E5	CONTROL DETAILS				
E6	POWER DETAILS				
E7	LIGHTING SCHEDULE AND AIC				
E8	PANEL SCHEDULES				
E9	SREB No.2 LIGHTING PLAN				
E10	SREB No.2 POWER PLAN				



THESE LEGENDS ARE STANDARD LEGENDS, ALL SYMBOLS SHOWN ON LEGENDS ARE NOT NECESSARILY ON THE DRAWING(S).

PS&E REVIEW




MBA CONSULTING ENGINEERS 3812 SPENARD ROAD, SUITE 20 ANCHORAGE, ALASKA 99517 (907) 274 - 2622 ERTIFICATE OF AUTHORIZATIO NO. AECC578 BY DATE REVISION


AND PUBLIC FACILITIES CENTRAL REGION 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590


09/09/2022

E1 of E10


KWETHLUK AIRPORT STATE OF ALASKA KWETHLUK, ALASKA SNOW REMOVAL EQUIPMENT BUILDINGS **DEPARTMENT OF TRANSPORTATION** PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023 ELECTRICAL LEGENDS







\HEATING CONTROL WIRING DIAGRAM NTS (THIS DETAIL APPLIES TO BOTH SREBS)



2 PADDLE FAN CONTROL DIAGRAM E5 /NTS (THIS DETAIL APPLIES TO BOTH SREBS)

NOTES - DETAIL 1

- 1) PLUG-IN RELAY WITH 120V COIL, DPDT CONTACTS, SCREW TERMINAL BASE. SQUARE D CLASS 8501 KUR12V120 RELAY, 8501NR8B BASE, 8501NH82 HOLD DOWN CLIP. WALL MOUNT IN WEATHERPROOF ENCLOSURE OR APPROVED EQUAL.
- $\fbox{2}$ THERMOSTAT WIRE CAN RUN EXPOSED BUT MUST BE STAPLED TO WAINSCOT 24 INCHES O.C.
- THERMOSTAT FOR HEATER NON MERCURY TYPE. HIGH TEMPERATURE SET AT 65° F.
- SPRING-MOTOR, TIME INTERVAL SWITCH, BY DIV. 23, WITHOUT HOLD OPTION, WITH NORMALLY OPEN ISOLATED CONTACT RATED 15 AMPS @ 120 VOLTS, AND TIME INTERVAL 0-12 HOURS. MOUNT NEXT TO LATCH SIDE OF MAN DOOR 66 INCHES A.F.F., SEE NOTE 5 BELOW. PROVIDE SIGN THAT READS "HEAT CONTROL TIMER -HEATERS WILL RUN WHEN TIME REMAINING IS GREATER THAN
- (5) EXTERIOR THERMOSTAT SET TO CLOSE CONTACTS WHEN EXTERIOR TEMPERATURE IS BELOW 50°F. HONEYWELL T675A1136 CONTROLLER TEMPERATURE SENSOR OR AS APPROVED.
- $\fbox{6}$ KEYED (AUTO-ON) SWITCH (SHOWN IN AUTO POSITION). KEY THE SAME AS THE RECEPTACLE HOA SWITCH.
- 7. SEQUENCE OF OPERATION:

CONTACTS IN 4 ARE ENERGIZED WHEN OUTSIDE TEMPERATURE IS

THE CONTACTS IN THE TIME SWITCH 4 CLOSE WHEN THE SWITCH IS SET TO ANY TIME GREATER THAN ZERO.

RELAY CONTACTS CLOSE WHEN TIME SWITCH CONTACTS (1) CLOSE.


CONNECT RELAY CONTACTS IN SERIES WITH THERMOSTAT.

When the timer switch \bigoplus times out, its internal contact opens and burner ceases operation.

NOTES - DETAIL 2

- 1) ELECTRONIC SPEED CONTROL SUPPLIED OR RECOMMENDED BY THE PADDLE FAN MANUFACTURER.
- 2 SPRING-MOTOR, TIME INTERVAL SWITCH, BY DIV. 23, WITHOUT HOLD OPTION, WITH NORMALLY OPEN ISOLATED CONTACT RATED 15 AMPS @ 120 VOLTS, AND TIME INTERVAL 0-12 HOURS, MOUNT 66 INCHES A.F.F. PROVIDE SIGN THAT READS "FAN TIMER".

GRAPHIC SCALE: 1'-0" = 100'-0"



\UNIT HEATER WIRING DIAGRAM E5 NTS (THIS DETAIL APPLIES TO BOTH SREBS)

REVISION

PS&E REVIEW



MBA CONSULTING ENGINEERS 812 SPENARD ROAD, SUITE 20 ANCHORAGE, ALASKA 99517 (907) 274 - 2622 RTIFICATE OF AUTHORIZATIO NO. AECC578 BY DATE


STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT KWETHLUK, ALASKA SNOW REMOVAL EQUIPMENT BUILDINGS PROJECT No. CFAPT00801 AIP No. 3-02-0435-XXX-2023

CONTROL DETAILS

09/09/2022

E5 of E1(



	LUMINAIRE SCHEDULE							
CALLOUT	SYMBOL	TOTAL LUMEN	LUMEN/WATT	MOUNTING	DESCRIPTION	MODEL		
A/150		15,000	120	16'-0"	PENDANT MOUNT LED WITH POWER HOOK AND SAFETY CHAIN, WIDE DISTRIBUTION, NO SHIELDING, 120 VOLT, 80 CRI, 4000K CCT. FIXTURE STANDARD FINISH TO MATCH BUILDING FINISH AS CLOSELY AS POSSIBLE. SUITABLE FOR -40F, DAMP LOCATION LISTED.	LITHONIA IBL-15L-WD-LP840- SD125-USPOM		
B/20	五	2660	100	AS SHOWN ON PLANS	WALL MOUNT FULL CUTOFF LED. RATED FOR -40 DEGREES F.	DECO LIGHTING: D464-L-24-40-U-Z		
C/40		4417	129	WALL MOUNT 7'-0"AFF ABOVE BENCH	LOW PROFILE LENS Z STRIP, PROVIDE ANGLE BRACKET FOR MOUNTING ABOVE WORK BENCH.	LITHONIA ZL1N LED L48 ASR 5000LM FST MVOLT 40K 80CRI ZLANGBKT-USPOM		
E/60	Ŧ			8'-0"	EMERGENCY EGRESS LED LIGHT, Ni-MH BATTERY. 120V, -40°F RATING. AUTOTEST,	BEGHELLI USA LIGHTING: BOL-WP-12V27W 2 MR16LED		
ЕМ	424			8'-0"	SURFACE MOUNT REMOTE EMERGENCY LIGHT REMOTE HEAD. PROVIDE MR16LED LAMP, AND WIRE GUARD.	BEGHELLI USA LIGHTING: BOL-WP-R 2 MR16LED BPG9		

VERIFY CATALOG NUMBER WITH FIXTURE DESCRIPTION FOR ADDITIONAL REQUIREMENT.
MANUFACTURER NUMBER IS BASIS OF DESIGN SUBMIT SUBSTITUTIONS IN ACCORDANCE WITH GCP 60-08 FOR APPROVAL.

Transformer Assumptions

A.I.R. REQUIREMENTS

SHORT CIRCUIT AND SERVICE NOTES:

BASED ON THE FOLLOWING:

UTILITY	=	GENERIC	
TRANSFORMER SIZE	=	75	KVA
TRANSFORMER IMPEDANCE	=	1.08	% Z
ENGTH OF SERVICE CONDUCTORS	=	195	FEET

H OF SERVICE CONDUCTORS SERVICE CONDUCTOR SIZE #3/0 AWG NUMBER OF PARALLEL RUNS

CONDUIT TYPE Copper in Non-Metallic*

MOTOR CONTRIBUTION

AVAILABLE	SHORT	CIRCUIT	AMPS	SUMMARY

LOCATION	METER BASE	SREB1 DISCONNECT	PANEL C1	TRANSFER SW	PANEL G1	SREB2 DISCONNECT
SCA RMS	16,174	15,807	14,862	12,538	10,669	12,295
@ X/R	1.52	1.49	1.39	1.00	0.79	1.20
LOCATION	PANEL C2	TRANSFER SW	PANEL G2	EEB DISCONNECT		
SCA RMS	9,926	8,665	7,652	7,940		
@ X/R	0.84	0.71	0.61	0.54		

THE ABOVE DATA (OTHER THAN MOTOR LOAD) SHALL BE CONFIRMED WITH THE SERVING UTILITY BEFORE EQUIPMENT IS ORDERED. ANY VARIATIONS THAT MIGHT INCREASE AVAILABLE SHORT-CIRCUIT CURRENT SHALL BE REPORTED TO THE CONTRACTING AGENCY.

SERVICE EQUIPMENT SHALL HAVE AN INTEGRATED SHORT CIRCUIT RATING SUITABLE FOR THE AVAILABLE SCA. DOWNSTREAM EQUIPMENT AND CIRCUIT BREAKER AIC RATINGS MAY BE SATISFIED BY UTILIZING ONE OF THE FOLLOWING METHODS:

1. EQUIPMENT RATED FOR THE AVAILABLE SCA AT EACH POINT IN THE SYSTEM.

ARC FLASH CALCULATIONS					
	METERBASE	SREB#1 DISCONNECT	PANEL C1	TRANSFER SW#1	
ARC FLASH BOUNDARY	13'-4"	13'-3"	10'-0"	11'-6"	
INCIDENT ENERGY	39.44 CAL/CM^2	38.84 CAL/CM^2	24.79 CAL/CM^2	30.92 CAL/CM^2	
WORKING DISTANCE	18 INCHES	18 INCHES	18 INCHES	18 INCHES	
SHOCK HAZARD EXPOSURE	240 VAC	240 VAC	240 VAC	240 VAC	
INSULATING GLOVES CLASS	00 BEIGE	00 BEIGE	00 BEIGE	00 BEIGE	
LIMITED APPROACH BOUNDRY	3'-6"	3'-6"	3'-6"	3'-6"	
RESTRICTED APPROACH BOUNDRY	AVOID CONTACT	AVOID CONTACT	AVOID CONTACT	AVOID CONTACT	
PPE LEVEL	4	4	3	4	
CALCULATION DATE	8/9/2022				

ARC FLASH CALCULATIONS											
	PANEL G1	SREB#2 DISCONNECT	PANEL C2	TRANSFER SW#2							
ARC FLASH BOUNDARY	8'-5"	11'-6"	8'-1"	9'-5"							
INCIDENT ENERGY	18.76 CAL/CM ²	31.27 CAL/CM^2	17.76 CAL/CM^2	22.49 CAL/CM^2							
WORKING DISTANCE	18 INCHES	18 INCHES	18 INCHES	18 INCHES							
SHOCK HAZARD EXPOSURE	240 VAC	240 VAC	240 VAC	240 VAC							
INSULATING GLOVES CLASS	00 BEIGE	00 BEIGE	00 BEIGE	00 BEIGE							
LIMITED APPROACH BOUNDRY	3'-6"	3'-6"	3'-6"	3'-6"							
RESTRICTED APPROACH BOUNDRY	AVOID CONTACT	AVOID CONTACT	AVOID CONTACT	AVOID CONTACT							
PPE LEVEL	3	4	4	3							
CALCULATION DATE	8/9/2022										

ARC FLASH CALCULATIONS										
	PANEL G2	EEB DISCONNECT								
ARC FLASH BOUNDARY	6'-7"	8'-7"								
INCIDENT ENERGY	12.84 CAL/CM^2	19.33 CAL/CM^2								
WORKING DISTANCE	18 INCHES	18 INCHES								
SHOCK HAZARD EXPOSURE	240 VAC	240 VAC								
INSULATING GLOVES CLASS	00 BEIGE	00 BEIGE								
LIMITED APPROACH BOUNDRY	3'-6"	3'-6"								
RESTRICTED APPROACH BOUNDRY	AVOID CONTACT	AVOID CONTACT								
PPE LEVEL	3	3								
CALCULATION DATE	8/9/2022									

PS&E REVIEW

MBA CONSULTING ENGINEERS 3812 SPENARD ROAD, SUITE 200 Anchorage, Alaska 99517 (907) 274 - 2622 ERTIFICATE OF AUTHORIZATIO NO. AECC578 BY DATE

REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT
KWETHLUK, ALASKA
SNOW REMOVAL EQUIPMENT BUILDINGS
PROJECT No. CFAPT00801
AIP No. 3-02-0435-XXX-2023 LIGHTING SCHEDULE AND AIC

09/09/2022

E7 of E10

PANEL: C1	MOUNTING MAINS				<u>OPTIONS</u>					
PROJECT: KWETHLUK	SURFACE		LUGS			SOLID NEUTRAL GROUND BUS BAR				
LOCATION: SREB #1										
VOLTAGE: 240/120 VOLT	1 PHASE		3 WIRE		200	200 A		MLO	24k AIC	
CIRCUIT DESCRIPTION	KVA	AMP	Р	CKT	СКТ	AMP	Р	KVA	CIRCUIT DESCRIPTION	
PANEL G1	6.1	50	2	1	2	30	1	2.9	NEMA 5-30 RECEPTACLE	
PANEL GT		30		3	4	30	2		SPARE	
50 AMP 240 VOLT RECEPTACLE NEMA	9.6	50	2	5	6	30			SFARE	
6-50		30	2	7	8	- 30	2		SPARE	
NEMA 5-20 RECEPTACLES	0.7	20	1	9	10	30	-		SPARE	
NEMA 5-20 RECEPTACLES	0.5	20	1	11	12	20	1	0.2	NEMA 5-20 - COMPRESSOR	
AID COMPDESSOR & UD	6.4	- 60	2	13	14	15	1	0.1	PADDLE FAN	
AIR COMPRESSOR 5 HP		1 80		15	16	20	1		SPARE	
SPARE		20	1	17	18	20	1		SPARE	
SPARE		20	1	19	20	20	1		SPARE	
SPARE		20	1	21	22	20	1		SPARE	
SPARE		20	1	23	24	20	1		SPARE	
SPARE		20	1	25	26	20	1		SPARE	
SPACE				27	28				SPACE	
SPACE				29	30				SPACE	
CONNECTED LOAD:		26.5	KVA	110.5	А	REMARK				
DEMAND LOAD:		28.3	KVA	118.1	А	(1) PROVIDE SEPARATE NEUTRAL AND EQUIPMENT GROUND BA (2) PROVIDE MULTIPOLE CIRCUIT BREAKERS OR CIRCUIT				
									TIES, AS REQUIRED FOR COMPLIANCE	
DATE:						WITH NEC 210.4(B), WHEREVER FIELD WIRING RESULTS IN MULITWIRE BRANCH CIRCUITS.				
REV:						(3) DEMAND LOAD IS BASED ON NEC ARTICLE 220.				

PANEL: G1	MOUN	MOUNTING MAINS				<u>OPTIONS</u>					
PROJECT: KWETHLUK LOCATION: SREB #1	SURF	ACE		LUGS			SOLID NEUTRAL GROUND BUS BAR				
VOLTAGE: 240/120 VOLT	1 PH.	1 PHASE 3 WIRE		100 A		MLO		22k AIC			
CIRCUIT DESCRIPTION	KVA	AMP	Р	CKT	СКТ	AMP	Р	KVA	CIRCUIT DESCRIPTION		
INTERIOR LIGHTING	0.9	20	1	1	2	20	1	0.5	BENCH RECEPTACLES		
EXTERIOR LIGHTING	0.1	20	1	3	4	20	1	0.1	BENCH LIGHTING		
UH-2 UNIT HEATER (1/3HP)	0.8	15	1	5	6	20	1		SPARE		
UH-1 UNIT HEATER (1/3HP)	0.8	15	1	7	8	20	1	1.2	EXHAUST FAN EF-1 (1/2HP)		
SPARE		15	1	9	10	15	1	0.8	DAY TANK PUMP (1/3HP)		
SPARE		20	1	11	12	15	1	0.8	DAY TANK PUMP (1/3HP)		
SPARE		20	1	13	14	20	1		SPARE		
SPARE		20	1	15	16	20	1		SPARE		
CONNECTED LOAD:		6.1	KVA	25.3	А	REMARK (1) PROV		EPARATE N	IEUTRAL AND EQUIPMENT GROUND BARS.		
DEMAND LOAD:		6.6	KVA	27.7	А	(2) VERIFY CIRCUIT BREAKERS REQUIREMENTS FOR FUEL DISPENSER.					
							(3) PROVIDE MULTIPOLE CIRCUIT BREAKERS OR CIRCUIT				
DATE:								BREAKERS WITH HANDLE TIES, AS REQUIRED FOR COMPLIANCE WITH NEC 210.4(B), WHEREVER FIELD WIRING RESULTS IN			
REV:	MULITWIRE BRANCH CIRCUITS. (4) DEMAND LOAD IS BASED ON NEC ARTICAL 220.										

PANEL: C2	MOUNTING MAINS				<u>OPTIONS</u>						
PROJECT: KWETHLUK	SURFACE		LUGS			SOLID NEUTRAL GROUND BUS BAR					
LOCATION: SREB #2											
VOLTAGE: 240/120 VOLT	1 PHASE		3 WIRE		200	Α	MLC		24k AIC		
CIRCUIT DESCRIPTION	KVA	AMP	Р	CKT	CKT	AMP	Р	KVA	CIRCUIT DESCRIPTION		
PANEL G2	6.9	50	2	1	2	30	1	2.9	NEMA 5-30 RECEPTACLE		
PANEL G2		50		3	4		2		SPARE		
50 AMP 240 VOLT RECEPTACLE NEMA	9.6	50	_	5	6	30			SPARE		
6-50		50	2	7	8	30			SPARE		
NEMA 5-20 RECEPTACLES	0.7	20	1	9	10	30	2		SPARE		
NEMA 5-20 RECEPTACLES	0.5	20	1	11	12	20	1	0.2	NEMA 5-20 - COMPRESSOR		
AIR COMPRESSOR 5 HP	6.4	60	2	13	14	15	1	0.1	PADDLE FAN		
				15	16	20	1		SPARE		
SPARE		20	1	17	18	20	1		SPARE		
SPARE		20	1	19	20	20	1		SPARE		
SPARE		20	1	21	22	20	1		SPARE		
SPARE		20	1	23	24	20	1		SPARE		
SPARE		20	1	25	26	20	1		SPARE		
SPACE				27	28				SPACE		
SPACE				29	30				SPACE		
CONNECTED LOAD:		27.3	KVA	113.8	А	REMARKS:					
DEMAND LOAD:		29.2	KVA	121.6	Α	(1) PROVIDE SEPARATE NEUTRAL AND EQUIPMENT GROUND BARS. (2) PROVIDE MULTIPOLE CIRCUIT BREAKERS OR CIRCUIT					
								BREAKERS WITH HANDLE TIES, AS REQUIRED FOR COMPLIANCE			
DATE:						WITH NEC 210.4(B), WHEREVER FIELD WIRING RESULTS IN MULITWIRE BRANCH CIRCUITS.					
REV:								(3) DEMAND LOAD IS BASED ON NEC ARTICLE 220.			

PANEL: G2	MOUNTING MAINS				<u>OPTIONS</u>						
PROJECT: KWETHLUK LOCATION: SREB #2	- SURFACE LUGS					SOLID NEUTRAL GROUND BUS BAR					
VOLTAGE: 240/120 VOLT	1 PHASE 3 WIRE		100 A		MLO		22k AIC				
CIRCUIT DESCRIPTION	KVA	AMP	Р	СКТ	CKT	AMP	Р	KVA	CIRCUIT DESCRIPTION		
INTERIOR LIGHTING	0.9	20	1	1	2	20	1	0.5	BENCH RECEPTACLES		
EXTERIOR LIGHTING	0.1	20	1	3	4	20	1	0.1	BENCH LIGHTING		
UH-2 UNIT HEATER (1/3HP)	0.8	15	1	5	6	20	1		SPARE		
UH-1 UNIT HEATER (1/3HP)	0.8	15	1	7	8	20	1	1.2	EXHAUST FAN EF-1 (1/2HP)		
PMP-1 (1/3HP) FUEL PUMP AND DISPENSER	0.8	15	1	9	10	15	1	0.8	DAY TANK PUMP (1/3HP)		
SPARE		20	1	11	12	15	1	0.8	DAY TANK PUMP (1/3HP)		
SPARE		20	1	13	14	20	1		SPARE		
SPARE		20	1	15	16	20	1		SPARE		
CONNECTED LOAD:		6.9	KVA	28.6	Α	REMARKS: (1) PROVIDE SEPARATE NEUTRAL AND EQUIPMENT GROUND					
DEMAND LOAD:		7.4	KVA	31.0	Α	(2) VERIFY CIRCUIT BREAKERS REQUIREMENTS FOR FUEL DISPENSER.					
							(3) PROVIDE MULTIPOLE CIRCUIT BREAKERS OR CIRCUIT BREAKERS WITH HANDLE TIES. AS REQUIRED FOR COMPLIANCE				
DATE:							WITH NEC 210.4(B), WHEREVER FIELD WIRING RESULTS IN MULITWIRE BRANCH CIRCUITS. (4) DEMAND LOAD IS BASED ON NEC ARTICAL 220.				
REV:											

PS&E REVIEW



MBA CONSULTING ENGINEERS 3812 SPENARD ROAD, SUITE 200 ANCHORAGE, ALASKA 99517 (907) 274 - 2622 ERTIFICATE OF AUTHORIZATION
NO. AECC578 BY DATE REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES CENTRAL REGION 4111 AVIATION AVE., ANCHORAGE ALASKA 99502 PHONE (907) 269-0590

KWETHLUK AIRPORT

KWETHLUK, ALASKA

SNOW REMOVAL EQUIPMENT BUILDINGS

PROJECT No. CFAPT00801

AIP No. 3-02-0435-XXX-2023 PANEL SCHEDULES

09/09/2022 E8 of E10

