

# MOTORCYCLE CAUTION SIGN

#### MOTORCYCLE CAUTION NOTES:

- 1. BORDER DIMENSIONS: R=3", TH=1.25", IN=0.75"
- 2. PROVIDE XX EACH ON WINDMASTER STANDS AS MOVEABLE CONSTRUCTION SIGNS AT LOCATIONS DETERMINED BY THE ENGINEER.



### PROJECT INFORMATION SIGN

## PROJECT INFORMATION NOTES:

- 1. SIGN FONT: SERIES 2000
- 2. PROVIDE XX EACH ON 4"x4" POSTS AS PERMANENT CONSTRUCTION SIGNS AT LOCATIONS DETERMINED BY THE ENGINEER.



## **GROOVED PAVEMENT SIGN**

#### **GROOVED PAVEMENT NOTES:**

- 1. BORDER DIMENSIONS: R=3", TH=1.25", IN=0.75"
- 2. PROVIDE XX EACH ON WINDMASTER STANDS AS MOVEABLE CONSTRUCTION SIGNS AT LOCATIONS DETERMINED BY THE ENGINEER.

The way it is supposed to be done if the warning is intended to be primarily for motorcyclists is to mount the W8-15P plaque below the condition warning sign (example from MUTCD below). (2009 MUTCD 6F.54; MUTCD 11th edition 6H.34)



STATE OF ALASKA DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES

PROJECT DESIGNATION

XXXXXXX/XXXXXXXXXX

20XX

Χ

STATE ALASKA

PROJECT TITLE PROJECT TITLE

PERMANENT CONSTRUCTION SIGNS